Voltage Detectors Safety

Measuring instruments of low voltage



635 Professional multimeter CTL-1000 with True RMS

Optical & Acoustic

Digital AC/DC, T-RMS clamp meter with automatic and manual ranges and a VFD frequency converter.

The CTL-1000 has a large 13 mm HD display with 6000 digits and a backlight for easy reading.

It has functions for measuring AC and DC voltage, AC and DC current, resistance, capacitance, temperature, low impedance voltage, continuity and NCV (non-contact voltage detection).

Code	Ref.	Box
635360	Multimeter CTL-1000	1

Technical information

Measurement of actual/real values

Non-contact voltage detection (NCV)

DC voltage: 6 V / 60 V / 600 V / 1000 V AC voltage: 6 V / 60 V / 600 V / 1000 V Alternating Current: 60 A / 600 A / 1000 A Direct Current: 60 A / 600 A / 1000 A

Resistance: $600 \Omega/6 K\Omega/60 K\Omega/600 K\Omega/6 M\Omega/60 M\Omega$ Capacitance: 60 nF/600 nF/6 uF/60 uF/600 uF/6 mF/60 mF/6

Frequency: 100 Hz / 1000 Hz / 10 KHz

Temperature measurements: °C/°F -20 ~ 1000°C / -4 ~ 1832°F

Continuity Test

LowZ DC: 1000 V / AC1000 V DCμA: 200 μA / VFD Clamp Ø: 40 mm

LED lamp

Memory Min / Max and peak values

Low battery indicator

Stores relative measurement data

Backlight

Weight: 314.5 g

Size: 246 × 85 × 40 mm
 Power supply: 3 × 1.5 V AAA batteries

Supplied with a nylon case for transport and storage. According with standards EN61010-1, EN61010-2-033, EN61326, CAT III 600 V / CAT IV 1000 V





Accessories included.

