

Hydraulic tools / Hydraulic heads and pumps

Hydraulic head with die set  
for bimetallic terminals 300/400 mm<sup>2</sup>

## 20203 KIT CH-20P

- The universal CH-20P 20-ton hydraulic head is designed for all types of crimping applications, including hexagonal crimping, deep punching, and circular crimping. Suitable for conductor cross-sections up to 630 mm<sup>2</sup> Cu/Al, and, with the use of different adapters, it ensures versatile compatibility.
- The KIT 413009 includes the adapter, die, and punch for crimping bimetallic terminals of 300 and 400 mm<sup>2</sup> (TDC/S-300, TDC/S-400, TBF-300, and TBF-400) in accordance with standards UNE 211024-2 and NF C33-090-1.
- Supplied with a carrying case.



### Available dies



**DPA-300/630 adapter for deep punching,**  
300/630 mm<sup>2</sup>  
Code: 406013



**DPD-300/400L deep punch die,**  
300/400 mm<sup>2</sup>  
Code: 406014



**DPP-300/400 5E punch for deep punching,**  
300/400 mm<sup>2</sup>  
Code: 406015

Code	Ref.	Crimping force	Rated pressure	Head dimensions	Briefcase dimensions	Weight cabezal	Head weight
413009	KC-CH-20P	200 kN	700 bar	305x116x95 mm	450x370x120 mm	6 kg	2.5 kg