


Hydraulic tools / Hydraulic heads and pumps

Hydraulic head 13T

### 20203 CH-13U

- Universal crimping head for all types of crimping, including deep stepped crimping.
- Made of specially treated steel.
- Flip-top head for easy positioning and insertion of the dies.
- Quick-lock, quick-release connection.
- Supplied with an adapter for hexagonal crimping.
- Supplied with a tool holder briefcase.



#### Available dies



#### HD13 copper and aluminium lugs and butt-connectors for hexagonal compression

Copper: up to 400 mm<sup>2</sup>  
 Aluminium: up to 300 mm<sup>2</sup>  
 Bimetallic: up to 240 mm<sup>2</sup>



#### CD13 copper and aluminium compression clamps for circular compression

Copper: Up to 185 mm<sup>2</sup>  
 Aluminium: Main up to 300 mm<sup>2</sup> and tap up to 70 mm<sup>2</sup>



#### MP-L/PP bimetallic cable lugs for deep punch compression

Up to 240 mm<sup>2</sup>

#### MP-S/PP aluminium multi-voltage joints for deep punch compression

Up to 240 mm<sup>2</sup>

**Note:** choose the adapter according to the cable section, to be used together with the corresponding punch and die.

Code	Ref.	Crimping force	Rated pressure	Head dimensions	Briefcase dimensions	Head weight	Briefcase weight
413000	CH-13U	130 kN	700 bar	248x93x76 mm	450x370x120 mm	3.5 kg	2.5 kg