

Multiuse Poles

Insulating Poles

SAFETY CATALOGUE



U
Universal Head



B
Bayonet Head



H
Hexagonal + Metric Head

IEC 60855
EN-50508



INDOOR and OUTDOOR *Use in humid environment*

Multiuse pole with only one section made of polyester and fibreglass tube Ø 32 mm and polyurethane foam filling with U (Universal), B (Bayonet) or H (Hexagonal) head.

Includes carrying bag.

According to IEC 60855 and EN-50508 standards.

618 BSC-M3

- Length: 1.5 meters
- Working voltage: 30 kV
- INDOOR and OUTDOOR use (Humid environment)

| Code | Ref. |
|--------|---------|
| 616700 | BSC-M3U |
| 616701 | BSC-M3B |
| 616702 | BSC-M3H |

618 BSC-M4

- Length: 2 meters
- Working voltage: 45 kV
- INDOOR and OUTDOOR use (Humid environment)

| Code | Ref. |
|--------|---------|
| 616703 | BSC-M4U |
| 616704 | BSC-M4B |
| 616705 | BSC-M4H |

618 BSC-M5

- Length: 2.5 meters
- Working voltage: 66 kV
- INDOOR and OUTDOOR use (Humid environment)

| Code | Ref. |
|--------|---------|
| 616706 | BSC-M5U |
| 616707 | BSC-M5B |
| 616708 | BSC-M5H |

618 BSC-M6

- Length: 3 meters
- Working voltage: 132 kV
- INDOOR and OUTDOOR use (Humid environment)

| Code | Ref. |
|--------|---------|
| 616709 | BSC-M6U |
| 616710 | BSC-M6B |
| 616711 | BSC-M6H |