Insulating poles / Pole UNE 50508 - 1 section

Indoor and outdoor
use in humid environment

Multi-use poles compliant with the EN 50508 standard, made in a single section. Manufactured from a Ø 32 mm polyester and fibreglass tube and filled with polyurethane foam that complies with the IEC 60855 standard.
Head options: U (Universal), B (Bayonet), H (Hexagonal).
Supplied with carrying bags.





U
Universal head



B
Bayonet head



H
Hexagonal head

30806 BSC-M3

- Total length: 1.5 m
- For INDOOR and OUTDOOR use in humid environments

Code	Ref.	Working voltage
616700	BSC-M3U	30 kV
616701	BSC-M3B	
616702	BSC-M3H	

30806 BSC-M4

- Total length: 2 m
- For INDOOR and OUTDOOR use in humid environments

Code	Ref.	Working voltage
616703	BSC-M4U	45 kV
616704	BSC-M4B	
616705	BSC-M4H	

30806 BSC-M5

- Total length: 2.5 m
- For INDOOR and OUTDOOR use in humid environments

Code	Ref.	Working voltage
616706	BSC-M5U	66 kV
616707	BSC-M5B	
616708	BSC-M5H	

30806 BSC-M6

- Total length: 3 m
- For INDOOR and OUTDOOR use in humid environments

Code	Ref.	Working voltage
616709	BSC-M6U	132 kV
616710	BSC-M6B	
616711	BSC-M6H	