

Insulating Poles

Safety

Pole UNE 50508 - 1 section



M
Metric-10 Head



B
Bayonet Head



H
Hexagonal Head

IEC 60855
UNE-EN-50508



INDOOR and OUTDOOR Use in humid environment

Multise poles according to EN-50508 standard of 1 single-section. Manufactured with a Ø 32 mm polyester and fiberglass tube and filled with polyurethane foam that complies with the IEC 60855 standard.
Head: U (Universal), B (Bayonet), H (Hexagonal)
Includes carrying bag.

30806 BSC-M3

- Total length: 1.5 meters
- Working voltage: 30 kV
- For INDOOR and OUTDOOR use (humid environment)

Code	Ref.
616700	BSC-M3U
616701	BSC-M3B
616702	BSC-M3H

30806 BSC-M4

- Total length: 2 meters
- Working voltage: 45 kV
- For INDOOR and OUTDOOR use (humid environment)

Code	Ref.
616703	BSC-M4U
616704	BSC-M4B
616705	BSC-M4H

30806 BSC-M5

- Total length: 2.5 meters
- Working voltage: 66 kV
- For INDOOR and OUTDOOR use (humid environment)

Code	Ref.
616706	BSC-M5U
616707	BSC-M5B
616708	BSC-M5H

30806 BSC-M6

- Total length: 3 meters
- Working voltage: 132 kV
- For INDOOR and OUTDOOR use (humid environment)

Code	Ref.
616709	BSC-M6U
616710	BSC-M6B
616711	BSC-M6H