

Connectable Multiuse Poles

Insulating Poles

SAFETY CATALOGUE



U
Universal Head



B
Bayonet Head



H
Hexagonal + Metric Head

IEC 60855
EN-50508



INDOOR and OUTDOOR *Use in humid environment*

Connectable multiuse pole with two or three sections made of polyester and fibreglass tube Ø 32 mm and polyurethane foam filling with U (Universal), B (Bayonet) or H (Hexagonal) head.
Includes carrying bag.
According to IEC 60855 and EN-50508 standards.

Mod. BSC-M22

- Total length: 2 meters
- Composed of 2 sections of 1 m each
- Working voltage: 45 kV
- INDOOR and OUTDOOR use (Humid environment)

Code	Ref.
616712	BSC-M22U
616713	BSC-M22B
616714	BSC-M22H

Mod. BSC-M32

- Total length: 2.5 meters
- Composed of 1 section of 1 m + 1 section of 1.5 m
- Working voltage: 66 kV
- INDOOR and OUTDOOR use (Humid environment)

Code	Ref.
616715	BSC-M32U
616716	BSC-M32B
616717	BSC-M32H

Mod. BSC-M33

- Total length: 3 meters
- Composed of 2 sections of 1.5 m each
- Working voltage: 132 kV
- INDOOR and OUTDOOR use (Humid environment)

Code	Ref.
616718	BSC-M33U
616719	BSC-M33B
616720	BSC-M33H

Mod. BSC-M222

- Total length: 3 meters
- Composed of 3 sections of 1 m each
- Working voltage: 132 kV
- INDOOR and OUTDOOR use (Humid environment)

Code	Ref.
616721	BSC-M222U
616722	BSC-M222B
616723	BSC-M222H