

Insulating Poles

Safety

Connectable pole UNE 50508

*INDOOR and OUTDOOR
Use in humid environment*

Multiuse poles according to EN-50508 standard of two or three-section. Manufactured with a Ø 32 mm polyester and fiberglass tube and filled with polyurethane foam that complies with the IEC 60855 standard. Head: U (Universal), B (Bayonet), H (Hexagonal). Includes carrying bag.



U
Universal Head



B
Bayonet Head



H
Hexagonal Head

IEC 60855
UNE-EN-50508



30807 BSC-M22

- Total linked length: 2 meters
- Composed of 2 sections of 1 m each
- Working voltage: 45 kV
- For INDOOR and OUTDOOR use (humid environment)

Code	Ref.
616712	BSC-M22U
616713	BSC-M22B
616714	BSC-M22H

30807 BSC-M32

- Total linked length: 2.5 meters
- Composed of 1 section of 1 m + 1 section of 1.5 m
- Working voltage: 66 kV
- For INDOOR and OUTDOOR use (humid environment)

Code	Ref.
616715	BSC-M32U
616716	BSC-M32B
616717	BSC-M32H

30807 BSC-M33

- Total linked length: 3 meters
- Composed of 2 sections of 1.5 m each
- Working voltage: 132 kV
- For INDOOR and OUTDOOR use (humid environment)

Code	Ref.
616718	BSC-M33U
616719	BSC-M33B
616720	BSC-M33H

30807 BSC-M222

- Total linked length: 3 meters
- Composed of 3 sections of 1 m each
- Working voltage: 132 kV
- For INDOOR and OUTDOOR use (humid environment)

Code	Ref.
616721	BSC-M222U
616722	BSC-M222B
616723	BSC-M222H