Insulating poles / Connectable pole UNE 50508

Indoor and outdoor
use in humid environment

Multiuse poles compliant with the EN-50508 standard, available in two or three sections. Manufactured from Ø 32 mm polyester and fibreglass tube and filled with polyurethane foam that complies with the IEC 60855 standard.
Head: U (Universal), B (Bayonet), H (Hexagonal).
Supplied with carrying bag.





U
Universal head



B
Bayonet head



H
Hexagonal head

30807 BSC-M22

- Total linked length: 2 m
- Composed of 2 sections of 1 m each
- For INDOOR and OUTDOOR use in humid environments

Code	Ref.	Working voltage
616712	BSC-M22U	45 kV
616713	BSC-M22B	
616714	BSC-M22H	

30807 BSC-M32

- Total linked length: 2.5 m
- Composed of 1 section of 1 m + 1 section of 1.5 m
- For INDOOR and OUTDOOR use in humid environments

Code	Ref.	Working voltage
616715	BSC-M32U	66 kV
616716	BSC-M32B	
616717	BSC-M32H	

30807 BSC-M33

- Total linked length: 3 m
- Composed of 2 sections of 1.5 m each
- For INDOOR and OUTDOOR use in humid environments

Code	Ref.	Working voltage
616718	BSC-M33U	132 kV
616719	BSC-M33B	
616720	BSC-M33H	

30807 BSC-M222

- Total linked length: 3 m
- Composed of 3 sections of 1 m each
- For INDOOR and OUTDOOR use in humid environments

Code	Ref.	Working voltage
616721	BSC-M222U	132 kV
616722	BSC-M222B	
616723	BSC-M222H	