

Connectable Multiuse Poles

Insulating Poles

SAFETY CATALOGUE 2019

INDOOR and OUTDOOR Use in humid environment

Connectable multiuse pole with two or three sections, made of polyester and fibreglass tube Ø 38.4 mm and polyurethane foam filling with U (Universal) or B (Bayonet) head. Includes carrying bag.

According to IEC 60855 and EN-50508 standards.



U
Universal Head



B
Bayonet Head

IEC 60855
EN-50508



619 BSC-A43

- Total length: 3.5 meters
- Composed of 1 section of 2 m and 1 section of 1.5 m
- Working voltage: 132 kV
- INDOOR and OUTDOOR use (Humid environment)

| Code | Ref. |
|---------------|-----------------|
| 616724 | BSC-A43U |
| 616725 | BSC-A43B |

619 BSC-A44

- Total length: 4 meters
- Composed of 2 sections of 2 m each
- Working voltage: 220 kV
- INDOOR and OUTDOOR use (Humid environment)

| Code | Ref. |
|---------------|-----------------|
| 616726 | BSC-A44U |
| 616727 | BSC-A44B |

619 BSC-A54

- Total length: 4.5 meters
- Composed of 1 section of 2 m + 1 section of 2.5 m
- Working voltage: 220 kV
- INDOOR and OUTDOOR use (Humid environment)

| Code | Ref. |
|---------------|-----------------|
| 616728 | BSC-A54U |
| 616729 | BSC-A54B |

619 BSC-A55

- Total length: 5 meters
- Composed of 2 sections of 2.5 m each
- Working voltage: 380 kV
- INDOOR and OUTDOOR use (Humid environment)

| Code | Ref. |
|---------------|-----------------|
| 616730 | BSC-A55U |
| 616731 | BSC-A55B |

619 BSC-A66

- Total length: 6 meters
- Composed of 2 sections of 3 m each
- Working voltage: 380 kV
- INDOOR and OUTDOOR use (Humid environment)

| Code | Ref. |
|---------------|-----------------|
| 616732 | BSC-A66U |
| 616733 | BSC-A66B |

619 BSC-A444

- Total length: 6 meters
- Composed of 3 sections of 2 m each
- Working voltage: 380 kV
- INDOOR and OUTDOOR use (Humid environment)

| Code | Ref. |
|---------------|------------------|
| 616734 | BSC-A444U |
| 616735 | BSC-A444B |