

# Insulating Poles

## Safety

### Connectable poles



**M**  
Metric-10 Head



**U**  
Universal Head



**B**  
Bayonet Head



**P**  
Multipurpose Head  
(Hexagonal + Metric head-10)



### INDOOR and OUTDOOR Use in dry and humid environment

Connectable pole with two or three sections made with polyester and fibreglass tube Ø 38.4 mm with hand protector, grip, tip, 3 deflecting hoods and M (Metric-10), U (Universal), B (Bayonet) or P (Hexagonal + Metric-10) head.

#### 30805 BMAE-3V

- Total linked length: 3 meters
- Composed of 2 sections of 1.5 m each
- Working voltage: 110 kV
- For INDOOR and OUTDOOR use in dry and humid environment

Code	Ref.
616600	BMAE-3V/110M
616601	BMAE-3V/110U
616602	BMAE-3V/110B
616603	BMAE-3V/110P

#### 30805 BMAE-4V

- Total linked length: 4 meters
- Composed of 2 sections of 2 m each
- Working voltage: 220 kV
- For INDOOR and OUTDOOR use in dry and humid environment

Code	Ref.
616610	BMAE-4V/220M
616611	BMAE-4V/220U
616612	BMAE-4V/220B
616613	BMAE-4V/220P

#### 30805 BMAE-5V

- Total linked length: 5 meters
- Composed of 2 sections of 2 m + 1 section of 1 m
- Working voltage: 380 kV
- For INDOOR and OUTDOOR use in dry and humid environment

Code	Ref.
616620	BMAE-5V/380M
616621	BMAE-5V/380U
616622	BMAE-5V/380B
616623	BMAE-5V/380P

#### 30805 BMAE-6V

- Total linked length: 6 meters
- Composed of 3 sections of 2 m each
- Working voltage: 380 kV
- For INDOOR and OUTDOOR use in dry and humid environment

Code	Ref.
616630	BMAE-6V/380M
616631	BMAE-6V/380U
616632	BMAE-6V/380B
616633	BMAE-6V/380P