Insulating poles / Connectable poles

Indoor and outdoor
use in a dry environment

Connectable pole with two or three sections made of polyester and fibreglass tube Ø 38.4 mm, with hand protector, grip, tip, and M (Metric-10), U (Universal), B (Bayonet) or P (Hexagonal + Metric-10) head.

30804 BMAI-3V

- Total length: 3 m
- Composed of 2 sections of 1.5 m each
- For INDOOR and OUTDOOR use in dry environments

Code	Ref.	Working voltage
616500	BMAI-3V/132M	132 kV
616501	BMAI-3V/132U	
616502	BMAI-3V/132B	
616503	BMAI-3V/132P	

30804 BMAI-4V

- Total length: 4 m
- Composed of 2 sections of 2 m each
- For INDOOR and OUTDOOR use in dry environments

Code	Ref.	Working voltage
616510	BMAI-4V/220M	220 kV
616511	BMAI-4V/220U	
616512	BMAI-4V/220B	
616513	BMAI-4V/220P	

30804 BMAI-5V

- Total length: 5 meters
- Composed of 2 sections of 2 m + 1 section of 1 m
- For INDOOR and OUTDOOR use in dry environments

Code	Ref.	Working voltage
616520	BMAI-5V/380M	380 kV
616521	BMAI-5V/380U	
616522	BMAI-5V/380B	
616523	BMAI-5V/380P	

30804 BMAI-6V

- Total length: 6 m
- Composed of 3 sections of 2 m each
- For INDOOR and OUTDOOR use in dry environments

Code	Ref.	Working voltage
616530	BMAI-6V/380M	380 kV
616531	BMAI-6V/380U	
616532	BMAI-6V/380B	
616533	BMAI-6V/380P	

M
Metric 10 head

U
Universal head

B
Bayonet head

P
Multipurpose head
(Hexagonal + Metric-10)