

Insulating Poles

Safety

Connectable poles



M
Metric-10 Head



U
Universal Head



B
Bayonet Head



P
Multipurpose Head
(Hexagonal + Metric head-10)



INDOOR and OUTDOOR Use in dry and humid environment

Connectable pole with two sections made of polyester and fibreglass tube \varnothing 32 mm with humidity-proof seals on each end, hand protector, grip, tip, 3 deflecting hoods and M (Metric-10), U (Universal), B (Bayonet) or P (Hexagonal + Metric-10) head.

30805 BMAE-2

- Total length: 2 meters
- Composed of 2 sections of 1 m each
- Working voltage: 30 kV
- For INDOOR and OUTDOOR use

Code	Ref.
616200	BMAE-2/30M
616201	BMAE-2/30U
616202	BMAE-2/30B
616203	BMAE-2/30P

30805 BMAE-2,5

- Total length: 2.5 meters
- Composed of 1 section of 1 m + 1 section of 1.5 m
- Working voltage: 66 kV
- For INDOOR and OUTDOOR use

Code	Ref.
616210	BMAE-2,5/66M
616211	BMAE-2,5/66U
616212	BMAE-2,5/66B
616213	BMAE-2,5/66P

30805 BMAE-3

- Total length: 3 meters
- Composed of 2 sections of 1.5 m each
- Working voltage: 110 kV
- For INDOOR and OUTDOOR use

Code	Ref.
616220	BMAE-3/110M
616221	BMAE-3/110U
616222	BMAE-3/110B
616223	BMAE-3/110P