Insulating poles / Connectable poles

## Indoor and outdoor
# use in dry and humid environment

Connectable pole with two sections, made of polyester and fibreglass tube Ø 32 mm, with humidity-proof seals at both ends, hand guard, grip, tip, three deflecting hoods, and head options: M (Metric-10), U (Universal), B (Bayonet) or P (Hexagonal + Metric-10) head.



## 30805 BMAE-2

- Total length: 2 m
- Composed of 2 sections of 1 m each
- For INDOOR and OUTDOOR use in dry and humid environments

| Code | Ref. | Working voltage | Bells |
|---|---|---|---|
| 616200 | BMAE-2/30M | 30 kV | 3 |
| 616201 | BMAE-2/30U | | |
| 616202 | BMAE-2/30B | | |
| 616203 | BMAE-2/30P | | |

## 30805 BMAE-2,5

- Total length: 2.5 m
- Composed of 1 section of 1 m + 1 section of 1.5 m
- For INDOOR and OUTDOOR use in dry and humid environments

| Code | Ref. | Working voltage | Bells |
|---|---|---|---|
| 616210 | BMAE-2,5/66M | 66 kV | 3 |
| 616211 | BMAE-2,5/66U | | |
| 616212 | BMAE-2,5/66B | | |
| 616213 | BMAE-2,5/66P | | |

## 30805 BMAE-3

- Total length: 3 m
- Composed of 2 sections of 1.5 m each
- For INDOOR and OUTDOOR use in dry and humid environments

| Code | Ref. | Working voltage | Bells |
|---|---|---|---|
| 616220 | BMAE-3/110M | 110 kV | 3 |
| 616221 | BMAE-3/110U | | |
| 616222 | BMAE-3/110B | | |
| 616223 | BMAE-3/110P | | |



**M**
Metric 10 head



**U**
Universal head



**B**
Bayonet head



**P**
Multipurpose head
(Hexagonal + Metric-10)