Insulating poles / Connectable poles

Indoor and outdoor
use in a dry environment

Connectable poles with two sections, made of polyester and fibreglass tube Ø 32 mm, with humidity-proof seals at both ends, hand guard, grip, tip, and M (Metric-10), U (Universal), B (Bayonet) or P (Hexagonal + Metric-10) head.

30804 BMAI-2

- Total length: 2 m
- Composed of 2 sections of 1 m each
- For INDOOR and OUTDOOR use in dry environments

Code	Ref.	Working voltage
616100	BMAI-2/66M	66 kV
616101	BMAI-2/66U	
616102	BMAI-2/66B	
616103	BMAI-2/66P	

30804 BMAI-2,5

- Total length: 2.5 m
- Composed of 1 section of 1 m + 1 section of 1.5 m
- For INDOOR and OUTDOOR use in dry environments

Code	Ref.	Working voltage
616110	BMAI-2,5/110M	110 kV
616111	BMAI-2,5/110U	
616112	BMAI-2,5/110B	
616113	BMAI-2,5/110P	

30804 BMAI-3

- Total length: 3 m
- Composed of 2 sections of 1.5 m each
- For INDOOR and OUTDOOR use in dry environments

Code	Ref.	Working voltage
616120	BMAI-3/132M	132 kV
616121	BMAI-3/132U	
616122	BMAI-3/132B	
616123	BMAI-3/132P	

M
Metric 10 head

U
Universal head

B
Bayonet head

P
Multipurpose head
(Hexagonal + Metric-10)