

# Telescopic Poles

## Insulating Poles

SAFETY CATALOGUE

### INDOOR and OUTDOOR Use in dry environment

Telescopic pole with two sections made of reinforced fibreglass tube  $\varnothing$  37 and 30 mm with humidity-proof seals on each end, hand protector, grip, tip and M (Metric-10), U (Universal), B (Bayonet) or P (Hexagonal + Metric-10) head.

The length of each section can be adjusted as needed by means of an adjustment system with locking handles.



**M**  
Metric-10 Head



**U**  
Universal Head



**B**  
Bayonet Head



Easy  
Adjustment



**P**  
Hexagonal + Metric Head

### 615 BMTS-15/45

- Length folded: 0.85 meters
- Length extended: 1.486 meters
- Working voltage: 45 kV (fully extended)
- INDOOR and OUTDOOR use in dry environment
- Weight: 0.75 Kg

Code	Ref.
615300	BMTS-15/45M
615301	BMTS-15/45U
615302	BMTS-15/45B
615303	BMTS-15/45P

### 615 BMTS-20/66

- Length folded: 1.10 meters
- Length extended: 1.986 meters
- Working voltage: 66 kV (fully extended)
- INDOOR and OUTDOOR use in dry environment
- Weight: 0.95 Kg

Code	Ref.
615310	BMTS-20/66M
615311	BMTS-20/66U
615312	BMTS-20/66B
615313	BMTS-20/66P

### 615 BMTS-30/132

- Length folded: 1.65 meters
- Length extended: 3 meters
- Working voltage: 132 kV (fully extended)
- INDOOR and OUTDOOR use in dry environment
- Weight: 1.35 Kg

Code	Ref.
615320	BMTS-30/132M
615321	BMTS-30/132U
615322	BMTS-30/132B
615323	BMTS-30/132P

*Stable adjusters  
Adjust the extended length  
of each section as per your needs  
Last section foam filled for poles  
over 6 m according to IEC 60855  
Reinforced fibreglass tube  
Up to 12 m*