Insulating poles / Telescopic poles

Indoor and outdoor
use in a dry environment

Telescopic multi-section poles made of reinforced fibreglass and polyester tube with variable circular cross-section that allows each section to lock automatically. Final section of fibreglass and polyester tube filled with polyurethane foam with Universal head and manoeuvring hook.

Stable adjusters.
Final section filled with polyurethane foam according to IEC 60855 standard.

Easy adjustment

30803 BMTS-4/6

- Folded length: 1.75 m
- Extended length: 5.97 m (4 sections)
- Working voltage: 380 kV (fully extended)
- For INDOOR and OUTDOOR use in dry environments
- Weight: 3.40 kg

Code	Ref.	Sections	Working voltage
615325	BMTS-4/6	C+A	132 kV
		C+B+A	380 kV

30803 BMTS-5/9

- Folded length: 2.00 m
- Extended length: 8.75 m (5 sections)
- Working voltage: 420 kV (fully extended)
- For INDOOR and OUTDOOR use in dry environments
- Weight: 5.20 kg

Code	Ref.	Sections	Working voltage
615330	BMTS-5/9	D+A	132 kV
		D+B+A	380 kV
		D+C+B+A	420 kV

30803 BMTS-6/12

- Folded length: 2.30 m
- Extended length: 11.80 m (6 sections)
- Working voltage: 420 kV (fully extended)
- For INDOOR and OUTDOOR use in dry environments
- Weight: 7.25 kg

Code	Ref.	Sections	Working voltage
615335	BMTS-6/12	E+A	132 kV
		E+B+A	380 kV
		E+C+B+A	420 kV
		E+D+C+B+A	420 kV