

Personal Voltage Detector

Voltage Detectors

SAFETY CATALOGUE


Optical & Acoustic



635 Multimeter CAM

Optical & Acoustic

Multimeter with AC/DC non invasive amperimetric clamp up to 600 A.

Code	Ref.	 Box
635210	Multimeter CAM	1

Technical Details

<ul style="list-style-type: none"> ■ Display ■ AC Current ■ Accuracy ■ Highest Resolution ■ DC current ■ Accuracy ■ Highest Resolution ■ AC voltage ■ Accuracy ■ Highest Resolution ■ Input Impedance ■ DC voltage ■ Accuracy ■ Highest Resolution ■ Input Impedance ■ Frequency by clamp ■ Accuracy ■ Highest Resolution ■ Frequency by plugs ■ Accuracy ■ Highest Resolution ■ Duty Cycle ■ Frequency response ■ Resistance ■ Accuracy ■ Highest Resolution ■ Diode test ■ Resolution ■ Continuity test ■ Power Supply ■ Overload Category ■ Dimensions ■ Protection ■ Weight ■ Certifications ■ Colour ■ Scope of Delivery ■ Includes 	<p>MULTIMETER CAM</p> <p>4digit LCD, 6599counts 60A, 600A, 40 to 400Hz ±3,0%+10digits overall 10mA 60A, 600A ±3.0% +10digit overall 10mA 600mV, 6, 60, 600V, 40 to 400Hz ±1.5%+10digit till 600mV / ±1.2%+5digit till 60V / ±1.5%+10digit till 600V 100µV 10MΩ 600m, 6, 60, 600V ±0.8%+3digit till 60V / ±1.0%+5digit till 600V 100µV 10MΩ 600Hz, 1kHz, >1A AC rms ±1,5%+5digit till 1kHz 100mHz 600Hz, 6kHz, 10kHz, >0,2V AC rms ±1,5%+5digit till 10kHz 100mHz 10 to 95%, ±3,0%, >1A AC rms 10Hz to 1kHz 600, 6k, 60k, 600k, 6M, 60MΩ ±1.2%+2digit till 6MΩ ±2.0%+5digit till 60MΩ 100mΩ forward current ~1mA, drop voltage ~3,3V 1mV buzzer if resistance under 30Ω 3x 1.5V CAT III 600V 220 x 75 x 35mm IP44 340g TÜV/GS red 1x measuring lines 1 battery 1.5V, AAA, LR03</p>
--	---

3 years manufacturer's warranty.
According to EN 61010-2-032 standard.