

Personal Voltage Detector

Voltage Detectors

SAFETY CATALOGUE

Optical & Acoustic



Mod. Multimeter CAM

Optical & Acoustic

Multimeter with AC/DC non invasive amperimetric clamp up to 600 A.

Code	Ref.	Box
635210	Multimeter CAM	1

Technical Details

- Display
- AC Current
- Accuracy
- Highest Resolution
- DC current
- Accuracy
- Highest Resolution
- AC voltage
- Accuracy
- Highest Resolution
- Input Impedance
- DC voltage
- Accuracy
- Highest Resolution
- Input Impedance
- Frequency by clamp
- Accuracy
- Highest Resolution
- Frequency by plugs
- Accuracy
- Highest Resolution
- Duty Cycle
- Frequency response
- Resistance
- Accuracy
- Highest Resolution
- Diode test
- Resolution
- Continuity test
- Power Supply
- Overload Category
- Dimensions
- Protection
- Weight
- Certifications
- Colour
- Scope of Delivery
- Includes

MULTIMETER CAM

- 4digit LCD, 6599counts
- 60A, 600A, 40 to 400Hz
- ±3,0%+10digits overall
- 10mA
- 60A, 600A
- ±3.0% +10digit overall
- 10mA
- 600mV, 6, 60, 600V, 40 to 400Hz
- ±1.5%+10digit till 600mV / ±1.2%+5digit till 60V / ±1.5%+10digit till 600V
- 100µV
- 10MΩ
- 600m, 6, 60, 600V
- ±0.8%+3digit till 60V / ±1.0%+5digit till 600V
- 100µV
- 10MΩ
- 600Hz, 1kHz, >1A AC rms
- ±1,5%+5digit till 1kHz
- 100mHz
- 600Hz, 6kHz, 10kHz, >0,2V AC rms
- ±1,5%+5digit till 10kHz
- 100mHz
- 10 to 95%, ±3,0%, >1A AC rms
- 10Hz to 1kHz
- 600, 6k, 60k, 600k, 6M, 60MΩ
- ±1.2%+2digit till 6MΩ ±2.0%+5digit till 60MΩ
- 100mΩ
- forward current ~1mA, drop voltage ~3,3V
- 1mV
- buzzer if resistance under 30Ω
- 3x 1.5V
- CAT III 600V
- 220 x 75 x 35mm
- IP44
- 340g
- TÜV/GS
- red
- 1x measuring lines
- 1 battery 1.5V, AAA, LR03

3 years manufacturer's warranty.
According to EN 61010-2-032 standard.