

**Gloves / Leather overgloves**

**30301 SG**

Leather overgloves must be worn over dielectric gloves to protect them against mechanical risks and potential electric-arc hazards. These cowhide leather gloves with winged thumbs feature a 10 cm cuff with an adjustable Velcro tightening strap on the back of the hand.

The full-grain cowhide leather is silicone-treated to enhance its water-repellent properties.

**CE** According to EN 388:2016/A1:2018, EN 407:2020 and EN ISO 21420:2020 standards. Category III PPE.



Code	Ref.	Cross-reference utilization with dielectric gloves							EN 388	EN ISO 21420:2020	EN 407
		Dielectric gloves size and class									
		Size	00	0	1	2	3	4			
540113	SG-B	7	●	●	●	●			 <p><b>Levels of mechanical resistance:</b>                      Abrasion: <b>3</b>                      Blade cut: <b>1</b>                      Tear: <b>2</b>                      Puncture: <b>1</b>                      Cut by sharp object: <b>A</b></p>	<p><b>Ergonomics, design, safety, comfort and dexterity.</b></p>	<p><b>Technical resistance levels:</b>                      Molten metal mass: <b>X</b>                      Molten metal splash: <b>4</b>                      Radiant heat: <b>2</b>                      Convective heat: <b>2</b>                      Contact heat: <b>1</b>                      Flame: <b>4</b></p>
		8	●	●							
		9	●	●							
540114	SG-C	8			●	●					
		9			●	●					
		10	●	●							
540115	SG-D	10			●						
		11	●	●							
540116	SG-E	8					●	●			
		9					●	●			
		10				●					
		11			●						
540117	SG-F	12	●	●							
		10					●	●			
		11				●					
540118	SG-G	12			●						
		11					●	●			