
Earthing devices / Medium- and high-voltage overhead lines

Equipment with TML screw clamps - Ø 10-70 mm

30905 PATL-TML




TML screw clamps for cylindrical conductors; wide range of cable cross-sections and lengths to suit different short-circuit currents (ICC).


According to IEC 61230 standard



Composed of:

- 3 TML aluminium-alloy screw clamps. For cylindrical conductors with diameters between 10 and 70 mm.
- 3 copper PVC-insulated cables. Cross-section and length depending on model.
- 3 TT-50 earthing lathes.
- 3 bags for storing and transporting the equipment.







Cod. 630116
Operating hook.
Not included in the equipment.

Selection of the hot stick:
High-voltage earthing equipment is supplied without an insulating hot stick. The hot stick must be selected according to the system voltage, in accordance with applicable regulations, to ensure safe distances and proper ergonomics during operations.

Code	Ref.	Cable section (mm²)	Length (m)	Short circuit current Max. ICC
670176	PATL-TML/05006	50	6	12 kA/1s
670177	PATL-TML/05007		7	
670178	PATL-TML/05008		8	
670179	PATL-TML/05009		9	
670180	PATL-TML/05010		10	
670181	PATL-TML/05011		11	
670186	PATL-TML/07006	70	6	19 kA/1s
670187	PATL-TML/07007		7	
670188	PATL-TML/07008		8	
670189	PATL-TML/07009		9	
670190	PATL-TML/07010		10	
670191	PATL-TML/07011		11	
670196	PATL-TML/09506	95	6	25 kA/1s
670197	PATL-TML/09507		7	
670198	PATL-TML/09508		8	
670199	PATL-TML/09509		9	
670200	PATL-TML/09510		10	
670206	PATL-TML/12006	120	6	30 kA/1s
670207	PATL-TML/12007		7	
670208	PATL-TML/12008		8	
670209	PATL-TML/12009		9	
670210	PATL-TML/12010		10	
670216	PATL-TML/15006	150	6	40 kA/1s
670217	PATL-TML/15007		7	
670218	PATL-TML/15008		8	
670219	PATL-TML/15009		9	
670220	PATL-TML/15010		10	

* Depending on availability, the colour of the bag may vary.