Earthing devices / Medium- and high-voltage overhead lines

Equipment with PA40-B Bayonet clamps for large diameters

30905 PATL-PA40




PA40-B screw-type clamps with bayonet spindle for conductors or tubes with diameters from 36 to 130 mm, suitable for HV applications.


According to IEC 61230 standard.



Composed of:

- 3 PA40-B (Bayonet) aluminium alloy clamps with screw tightening, for cylindrical conductors with diameters between 36 and 130 mm.
- 3 copper cables with PVC insulation, section and length depending on model.
- 3 TT-50 earthing lathes.
- 3 nylon bags for storing and transporting the equipment.





Code	Ref.	Cable section (mm²)	Length (m)	Short-circuit current Max. ICC
674176	PATL-PA40/05006	50	6	12 kA/1s
674177	PATL-PA40/05007		7	
674178	PATL-PA40/05008		8	
674179	PATL-PA40/05009		9	
674180	PATL-PA40/05010		10	
674186	PATL-PA40/07006	70	6	19 kA/1s
674187	PATL-PA40/07007		7	
674188	PATL-PA40/07008		8	
674189	PATL-PA40/07009		9	
674190	PATL-PA40/07010		10	
674196	PATL-PA40/09506	95	6	25 kA/1s
674197	PATL-PA40/09507		7	
674198	PATL-PA40/09508		8	
674199	PATL-PA40/09509		9	
674200	PATL-PA40/09510		10	
674206	PATL-PA40/12006	120	6	30 kA/1s
674207	PATL-PA40/12007		7	
674208	PATL-PA40/12008		8	
674209	PATL-PA40/12009		9	
674210	PATL-PA40/12010		10	
674216	PATL-PA40/15006	150	6	40 kA/1s
674217	PATL-PA40/15007		7	
674218	PATL-PA40/15008		8	
674219	PATL-PA40/15009		9	
674220	PATL-PA40/15010		10	

* Depending on availability, the colour of the bag may vary.

Selection of the hot stick:
High-voltage earthing equipment is supplied without an insulating hot stick. The hot stick must be selected according to the system voltage, in accordance with applicable regulations, to ensure safe distances and proper ergonomics during operations.