Earthing devices / Low-voltage electric panels

Earthing and short-circuiting equipment with NH and MPUC blades

30902 ECBT-ID

Equipment with NH and MPUCN-type disconnecting blades, designed for low-voltage switchboards. Allows simultaneous connection of phases and neutral using an insulated pole, ensuring safe operation.

According to IEC 61230 standard.





NH00



NH1-3

Composed of:

- 3 NH00 disconnecting and earthing blades.
- 3 NH1-3 disconnecting and earthing blades.
- 3 copper PVC-insulated cables, 25 mm² cross-section, 0.45 m, 0.60 m, and 0.85 m long for phase short-circuiting.
- 1 copper PVC-insulated cable, 25 mm² cross-section, 0.75 m long for neutral.
- 1 copper PVC-insulated cable, 25 mm² cross-section, 1 m long for earthing.
- 1 insulated PTA neutral clamp.
- 1 MPUCN neutral clamp.
- 1 insulated pole for placing the blades.
- 1 TT-38A earthing lathe.
- 1 plastic case for storing and transporting the equipment.



MPUCN



PTA



TT-38A

Code	Ref.	Cable section (mm²)	Length (m)	Short-circuit current Max. ICC
659160	**ECBT-ID**	25	0.45 - 0.60 - 0.85 / 0.75	6.9 kA/1s