



*Quick connector  
to a hydraulic drive*

## i33 PP-130-H

- Hydraulic H type head with quick connection to a hydraulic drive with a maximum pressure of 700 bar.
- Included adapter for hexagonal compression
- Interchangeable dies.
- Tool holder briefcase included. Tool holder briefcase included.



Includes AD 13-C adapter to convert "H" head to "C" head.

Code	Ref.	Crimping force	Work pressure	Head dimensions	Briefcase dimensions	Head weight	Briefcase weight
421110	PP-130-H	130 KN	700 bar	78x263x70 mm	410x360x165 mm	3,4 Kg	1,6 Kg

Available dies



**U13-K** Copper and aluminium cable lugs and butt-connectors by hexagonal compression

Up to 400 mm<sup>2</sup> copper  
Up to 240 mm<sup>2</sup> aluminium



**U13-S/PZ** Copper cable lugs and butt-connectors and pin terminals by punching compression

Up to 300 mm<sup>2</sup> copper



**U13-DC/DA** Copper and aluminium Compression clamps by circular compression

Copper: Main up to 185 mm<sup>2</sup> and tap up to 95 mm<sup>2</sup>  
Aluminium: Main up to 300 mm<sup>2</sup> and tap up to 70 mm<sup>2</sup>



**MCB/PPR** Bimetallic cable lugs and aluminium low voltage joints by deep punching compression

Up to 240 mm<sup>2</sup>



**MC1S/PPR** Aluminium multi voltage joints by deep punching compression

Up to 240 mm<sup>2</sup>



**MC2S/PPR** Aluminium medium voltage joints by deep punching compression

Up to 240 mm<sup>2</sup>