

Battery Operated Hydraulic Cutting Tool

130 AS85



- Light and compact structure.
- Cutting head with snap closure; rotates 360°.
- High speed feed with double hydraulic cylinder.
- Pressure release button with single handed operation (on both sides, for left and right handed operators).
- Fastening ring for shoulder strap.
- Ergonomic grip for weight balance and easy and safe operation.
- Plastic housing, grip and pressure release button, insulating and shock resistant.
- Powerful led for working space illumination.



GM85
Fixed cutting blade
Weight: 150 g



SM85
Moveable cutting blade
Weight: 250 g



Code	Ref.	Cutting diameter	Tool dimensions	Tool weight
411165	AS85	max. Ø 85 mm	331x522x75 mm	7,2 Kg

Set dimensions	Set weight	Battery type	Battery changer	Shoulder stap
580x470x115 mm	10,7 Kg	18V/3,0 Ah LI-ION (RA50)	LG8	TG2

Cutting range table

Sector of use	Tensile strength N/mm ²	<Ø 30mm	Ø 35 mm	Ø 40 mm	Ø 45 mm	Ø 50 mm	Ø 55 mm	Ø 60 mm	Ø 65 mm	Ø 70 mm	Ø 75 mm	Ø 80 mm	Ø 85 mm
		Copper Cable	< 410	•	•	•	•	•	•	•	•	•	•
Aluminium Cable	< 210	•	•	•	•	•	•	•	•	•	•	•	•