



Electrohydraulic tool

Mod. AP130-H

- Portable electrohydraulic tool with rechargeable battery and C type head.
- 360° rotary head with quick opening.
- Two speeds: one fast to approach and one slow to crimp.
- Incorporates safety valve that limits the maximum pressure by means of an audible discharge. Quick return by discharge trigger.
- Includes tool holder briefcase.



Includes AD 13-C adapter to convert "H" head to "C" head.

Code	Ref.	Crimping force	Battery type	Battery changer	Set dimensions	Set weight
411102	AP130-H	130 KN	18V-3,0 Ah LI-ION-Battery-RA11	LG8	580x470x115 mm	10,0 Kg

Available dies



U13-K Copper and aluminium cable lugs and butt-connectors by hexagonal compression

Up to 300 mm² copper
Up to 240 mm² aluminium



U13-S/PZ Copper cable lugs and butt-connectors and pin terminals by punching compression

Up to 300 mm² copper



U13-DC/DA Copper and aluminium Compression clamps by circular compression

Copper: Main up to 185 mm² and tap up to 95 mm²
Aluminium: Main up to 300 mm² and tap up to 70 mm²



MCB/PPR Bimetallic cable lugs and aluminium low voltage joints by deep punching compression

Up to 240 mm²



MC1S/PPR Aluminium multi voltage joints by deep punching compression

Up to 240 mm²



MC2S/PPR Aluminium medium voltage joints by deep punching compression

Up to 240 mm²