



Hydraulic hand-tool

131 HPN-130-H

- Hydraulic hand-tool with H type head.
- 180° rotary head with quick opening.
- Incorporates audible safety valve that limits the maximum working force to 130KN.
- Two speeds: one fast to approach and one slow to crimp.
- Include tool holder briefcase.



Includes AD 13-C adapter to convert "H" head to "C" head.

Code	Ref.	Crimping force	Tool dimensions	Briefcase dimensions	Tool weight	Briefcase weight
411120	HPN-130-H	130 KN	540x160x75 mm	830x280x110 mm	5,6 Kg	2,1 Kg

Available dies



U13-K Copper and aluminium cable lugs and butt-connectors by hexagonal compression

Up to 400 mm² copper
Up to 240 mm² aluminium



U13-S/PZ Copper cable lugs and butt-connectors and pin terminals by punching compression

Up to 300 mm² copper




U13-DC/DA Copper and aluminium Compression clamps by circular compression

Copper: Main up to 185 mm² and tap up to 95 mm²
Aluminium: Main up to 300 mm² and tap up to 70 mm²



MCB/PPR Bimetallic cable lugs and aluminium low voltage joints by deep punching compression

Up to 240 mm²



MC1S/PPR Aluminium multi voltage joints by deep punching compression

Up to 240 mm²



MC2S/PPR Aluminium medium voltage joints by deep punching compression

Up to 240 mm²