Earthing Rods and Accessories



11301 Earthing rods 100 or 300 microns

Designed for fixed installations. these earthing rods are used to create a safe and stable earthing connection in electrical systems. They are manufactured from calibrated steel with an electrolytic copper plating treatment of 100 or 300 microns. The 100 μ rods with a diameter of 14.2 comply with UNE 202006 standards and have N AENOR certified.





Earthing rod 100µ - Ø 14.2 mm

Code	Ref.	Dimensions		l u l	1	
		L	D	Bag	Box	Pallet
T101415	Earthing rod 100 μ - Ø 14.2 Length 1.5 m	1.5 m	14.2 mm	10	100	400
T101420	Earthing rod 100 μ - Ø 14.2 Length 2.0 m	2.0 m	14.2 mm	10	100	400

Earthing rod 100µ - Ø 18.2 mm

Code	Ref.	Dimensions L D		₽ Bag	Box	Pallet
T101820	Earthing rod 100 μ - Ø 18.2 Length 2.0 m	2.0 m	18.2 mm	5	100	400

Earthing rod 300µ - Ø 14.6 mm

Code	Ref.	Dimensions		А	1	
	Tion.	L	D	Bag	Box	Pallet
T301420	Earthing rod 300 μ - Ø 14.6 Length 2.0 m	2.0 m	14.6 mm	10	100	400

