CE

11301 Earthing rods
Copper-coated earthing rods
100 or 300 microns

Earthing rods are designed for fixed installations to provide safe, effective, and long-lasting earthing.
Made from calibrated steel with an electrolytic copper coating of 100 or 300 microns for excellent corrosion resistance and durability.
100-micron rods (14.2 mm diameter) comply with UNE 202006 and carry AENOR N certification.

Earthing rod 100 µm - Ø 14.2 mm

Code	Ref.	Dimensions		Bag	Box	Pallet
		L	D			
T101415	Earthing rod 100 µm - Ø 14.2 Length 1.5 m	1.5 m	14.2 mm	10	100	400
T101420	Earthing rod 100 µm - Ø 14.2 Length 2.0 m	2.0 m	14.2 mm	10	100	400

Earthing rod 100 µm - Ø 18.2 mm

Code	Ref.	Dimensions		Bag	Box	Pallet
		L	D			
T101820	Earthing rod 100 µm - Ø 18.2 Length 2.0 m	2.0 m	18.2 mm	5	100	400

Earthing rod 300 µm - Ø 14.6 mm

Code	Ref.	Dimensions		Bag	Box	Pallet
		L	D			
T301420	Earthing rod 300 µm - Ø 14.6 Length 2.0 m	2.0 m	14.6 mm	10	100	400