


11301 Earthing rods


Copper-coated earthing rods
100 or 300 microns

Earthing rods are designed for fixed installations, providing safe, effective, and long-lasting earthing in electrical systems. They are manufactured from calibrated steel and coated with electrolytic copper of 100 or 300 μm , offering excellent corrosion resistance and durability even in harsh conditions.




According to UNE-EN IEC 62561-1:2023 and UNE 202006 standards and carry AENOR  certification.






CE






Earthing rod 100 μm - \varnothing 14.2 mm

Code	Ref.	Dimensions		 Bag	 Box	 Palet
		L	D			
T101415	Earthing rod 100 μm - \varnothing 14.2 - Length 1.5 m	1.5 m	14.2 mm	10	100	400
T101420	Earthing rod 100 μm - \varnothing 14.2 - Length 2.0 m	2.0 m	14.2 mm	10	100	400

Earthing rod 100 μm - \varnothing 18.2 mm

Code	Ref.	Dimensions		 Bag	 Box	 Palet
		L	D			
T101820	Earthing rod 100 μm - \varnothing 18.2 - Length 2.0 m	2.0 m	18.2 mm	5	100	400

Earthing rod 300 μm - \varnothing 14.6 mm

Code	Ref.	Dimensions		 Bag	 Box	 Palet
		L	D			
T301420	Earthing rod 300 μm - \varnothing 14.6 - Length 2.0 m	2.0 m	14.6 mm	10	100	400