


Cord End Terminals

Connections



10905 PF

Non-insulated cord end terminal

PF cord end terminal manufactured from electrolytic copper capillary tube with a tinplated finish to improve electrical contact.



Code	Ref.	Section (mm ²)	Dimensions (mm)					Kg x 1.000	Bag	Box
			L	L1	ØI	ØE	G			
265100	PF-0,50/6	0.50	6.1	5.3	1.3	2.1	0.15	0.020	100	6000
265110	PF-0,75/6	0.75	6.1	5.3	1.7	2.5	0.15	0.050	100	6000
265120	PF-1,00/10	1.00	10.0	9.3	1.4	2.5	0.15	0.070	100	6000
265140	PF-1,50/10	1.50	10.0	9.0	1.7	2.8	0.15	0.080	100	6000
265160	PF-2,50/10	2.50	10.0	9.0	2.2	3.4	0.15	0.090	100	5000
265190	PF-4,00/12	4.00	12.0	11.0	2.8	4.0	0.20	0.180	100	4000
265200	PF-6,00/12	6.00	12.0	11.0	3.5	4.7	0.20	0.230	100	3300
265220	PF-10,00/18	10.00	18.0	17.0	4.5	5.8	0.20	0.460	100	2000
265240	PF-16,00/18	16.00	18.0	17.0	5.8	7.5	0.20	0.650	100	1000
265255	PF-25,00/22	25.00	22.5	21.0	7.7	9.5	0.20	0.810	100	800
265258	PF-35,00/25	35.00	25.5	24.0	8.7	11.0	0.20	1.170	100	500
265265	PF-50,00/25	50.00	25.5	24.0	10.9	13.5	0.20	1.720	50	250