


# Cord End Terminals

## Connections



### 10901 APF

#### Cord end terminal

APF cord end terminal manufactured from electrolytic copper capillary tube with a tinplated finish to improve electrical contact. The insulating part is made of nylon (PA).




They feature an "Easy Enter" design, which facilitates the insertion of flexible copper wire, improving efficiency and accuracy during the crimping process.

Sec. (mm <sup>2</sup> )	L1	Code	Ref.	Colour	Dimensions (mm)						Kg x 1.000	Bag	Box
				F	L	L1	Ø11	G1	Ø12	G2			
0.50	8 10	245100	APF-0,50/8		14.5	8	1.0	0.15	2.6	0.25	0.088	100	4000
		260100	APF-0,50/10	WHITE	16.0	10	1.0	0.15	2.6	0.25	0.112	100	3500
0.75	8 12	245110	APF-0,75/8		14.6	8	1.2	0.15	2.8	0.25	0.100	100	4000
		260110	APF-0,75/12	BLUE	18.4	12	1.2	0.15	2.8	0.25	0.123	100	3500
1	8 12	245120	APF-1,00/8		14.6	8	1.4	0.15	3.0	0.25	0.116	100	3500
		260120	APF-1,00/12	RED	18.4	12	1.4	0.15	3.0	0.25	0.157	100	3000
1.5	8 18	245130	APF-1,50/8		14.6	8	1.7	0.15	3.5	0.25	0.134	100	3000
		260130	APF-1,50/18	BLACK	24.4	18	1.7	0.15	3.5	0.25	0.213	100	2500
2.5	8 18	245140	APF-2,50/8		15.2	8	2.2	0.15	4.0	0.25	0.165	100	2500
		260140	APF-2,50/18	GREY	25.0	18	2.2	0.15	4.0	0.25	0.258	100	2000
4	10 18	245150	APF-4,00/10		16.5	10	2.8	0.20	4.4	0.30	0.231	100	2000
		260150	APF-4,00/18	ORANGE	25.5	18	2.8	0.20	4.4	0.30	0.372	100	1600
6	12 18	245160	APF-6,00/12		20.0	12	3.5	0.20	6.3	0.30	0.388	100	1000
		260160	APF-6,00/18	GREEN	26.0	18	3.5	0.20	6.3	0.30	0.490	100	800
10	12 18	245170	APF-10,00/12		21.5	12	4.5	0.20	7.6	0.40	0.556	100	800
		260170	APF-10,00/18	BROWN	27.5	18	4.5	0.20	7.6	0.40	0.720	100	400
16	12 18	245180	APF-16,00/12		22.2	12	5.8	0.20	8.8	0.40	0.762	100	500
		260180	APF-16,00/18	IVORY	28.2	18	5.8	0.20	8.8	0.40	0.963	100	300
25	16 22	245190	APF-25,00/16		29.0	16	7.3	0.20	11.2	0.40	1.134	50	350
		260190	APF-25,00/22	IVORY	35.0	22	7.3	0.20	11.2	0.40	1.415	50	200
35	16 22	245200	APF-35,00/16		30.0	16	8.3	0.20	12.5	0.50	1.308	50	250
		260200	APF-35,00/22	RED	39.0	22	8.3	0.20	12.5	0.50	1.693	50	200
50	20 25	245210	APF-50,00/20		36.0	20	10.3	0.30	15.0	0.60	2.300	50	150
		260210	APF-50,00/25	BLUE	40.0	25	10.3	0.30	15.0	0.60	2.784	25	125

# Cord End Terminals

## Connections



### 10902 APF

#### Cord end terminal

APF cord end terminal manufactured from electrolytic copper capillary tube with a tinplated finish to improve electrical contact. The insulating part is made of nylon (PA).




They feature an "Easy Enter" design, which facilitates the insertion of flexible copper wire, improving efficiency and accuracy during the crimping process.

Sec. (mm <sup>2</sup> )	L1	Code	Ref.	Colour	Dimensions (mm)							Kg x 1.000	Bag	Box
				W	L	L1	ØI1	G1	ØI2	G2				
0.50	8	246100	APF-0,50W/8	ORANGE	14.5	8	1.0	0.15	2.6	0.25	0.088	100	4000	
	10	261100	APF-0,50W/10		16.0									10
0.75	8	246110	APF-0,75W/8	WHITE	14.6	8	1.2	0.15	2.8	0.25	0.100	100	4000	
	12	261110	APF-0,75W/12		18.4									12
1	8	246120	APF-1,00W/8	YELLOW	14.6	8	1.4	0.15	3.0	0.25	0.116	100	3500	
	12	261120	APF-1,00W/12		18.4									12
1.5	8	246130	APF-1,50W/8	RED	14.6	8	1.7	0.15	3.5	0.25	0.134	100	3000	
	18	261130	APF-1,50W/18		24.4									18
2.5	8	246140	APF-2,50W/8	BLUE	15.2	8	2.2	0.15	4.0	0.25	0.165	100	2500	
	18	261140	APF-2,50W/18		25.0									18
4	10	246150	APF-4,00W/10	GREY	16.5	10	2.8	0.20	4.4	0.30	0.231	100	2000	
	18	261150	APF-4,00W/18		25.5									18
6	12	246160	APF-6,00W/12	BLACK	20.0	12	3.5	0.20	6.3	0.30	0.388	100	1000	
	18	261160	APF-6,00W/18		26.0									18
10	12	246170	APF-10,00W/12	IVORY	21.5	12	4.5	0.20	7.6	0.40	0.556	100	800	
	18	261170	APF-10,00W/18		27.5									18
16	12	246180	APF-16,00W/12	GREEN	22.2	12	5.8	0.20	8.8	0.40	0.762	100	500	
	18	261180	APF-16,00W/18		28.2									18
25	16	246190	APF-25,00W/16	BROWN	29.0	16	7.3	0.20	11.2	0.40	1.134	50	350	
	22	261190	APF-25,00W/22		35.0									22
35	16	246200	APF-35,00W/16	BEIGE	30.0	16	8.3	0.20	12.5	0.50	1.308	50	250	
	22	261200	APF-35,00W/22		39.0									22
50	20	246210	APF-50,00W/20	OLIVE	36.0	20	10.3	0.30	15.0	0.60	2.300	50	150	
	25	261210	APF-50,00W/25		40.0									25

# Cord End Terminals

## Connections



### 10903 APF

#### Cord end terminal

APF cord end terminal manufactured from electrolytic copper capillary tube with a tinplated finish to improve electrical contact. The insulating part is made of nylon (PA).



They feature an "Easy Enter" design, which facilitates the insertion of flexible copper wire, improving efficiency and accuracy during the crimping process.

Sec. (mm <sup>2</sup> )	L1	Code	Ref.	Colour	Dimensions (mm)						Kg x 1.000	Bag	Box
					D	L	L1	Ø1	G1	Ø2			
0.50	8	245100	APF-0,50/8	WHITE	14.5	8	1.0	0.15	2.6	0.25	0.088	100	4000
	10	260100	APF-0,50/10		16.0								
0.75	8	250110	APF-0,75D/8	GREY	14.6	8	1.2	0.15	2.8	0.25	0.100	100	4000
	12	262110	APF-0,75D/12		18.4								
1	8	245120	APF-1,00/8	RED	14.6	8	1.4	0.15	3.0	0.25	0.116	100	3500
	12	260120	APF-1,00/12		18.4								
1.5	8	245130	APF-1,50/8	BLACK	14.6	8	1.7	0.15	3.5	0.25	0.134	100	3000
	18	260130	APF-1,50/18		24.4								
2.5	8	246140	APF-2,50W/8	BLUE	15.2	8	2.2	0.15	4.0	0.25	0.165	100	2500
	18	261140	APF-2,50W/18		25.0								
4	10	246150	APF-4,00W/10	GREY	16.5	10	2.8	0.20	4.4	0.30	0.231	100	2000
	18	261150	APF-4,00W/18		25.5								
6	12	250160	APF-6,00D/12	YELLOW	20.0	12	3.5	0.20	6.3	0.30	0.388	100	1000
	18	262160	APF-6,00D/18		26.0								
10	12	250170	APF-10,00D/12	RED	21.5	12	4.5	0.20	7.6	0.40	0.556	100	800
	18	262170	APF-10,00D/18		27.5								
16	12	250180	APF-16,00D/12	BLUE	22.2	12	5.8	0.20	8.8	0.40	0.762	100	500
	18	262180	APF-16,00D/18		28.2								
25	16	250190	APF-25,00D/16	YELLOW	29.0	16	7.3	0.20	11.2	0.40	1.134	50	350
	22	262190	APF-25,00D/22		35.0								
35	16	245200	APF-35,00/16	RED	30.0	16	8.3	0.20	12.5	0.50	1.308	50	250
	22	260200	APF-35,00/22		39.0								
50	20	245210	APF-50,00/20	BLUE	36.0	20	10.3	0.30	15.0	0.60	2.300	50	150
	25	260210	APF-50,00/25		40.0								