


Connections / Crimps

10702 CRC

Copper compression clamp

CRC branch connectors are manufactured from electrolytic copper and are used for copper-to-copper (Cu-Cu) connections and branches, mainly in earthing installations.

According to EN 62561-1 standard.



Code	Ref.	Main		Tap		Dimensions (mm)			Kg x 100	Bag	Box
		Max.	Min.	Max.	Min.	A	B	L			
145120	CRC-3	25	10	6	4	18.6	11.7	17.5	1.918	50	300
145130	CRC-4	25	16	10	4	19.5	11.8	17.6	1.774	50	300
145140	CRC-5	25	16	25	16	20.5	12.0	17.7	1.790	50	250
145150	CRC-6	35	35	25	4	25.2	15.5	21.1	3.848	25	125
145160	CRC-7	35	35	35	16	26.7	15.2	21.3	3.612	25	125
145170	CRC-8	70	50	35	4	33.3	20.4	27.2	9.315	10	60
145180	CRC-9	70	50	70	35	34.2	20.5	27.2	8.545	10	60
145190	CRC-10	95	70	35	16	41.9	23.8	29.1	14.795	10	40
145200	CRC-11	95	70	70	35	41.0	25.1	29.4	14.002	10	40
145210	CRC-12	95	95	95	95	39.8	25.0	29.1	12.039	10	40
145220	CRC-13	120	120	120	25	44.1	27.2	30.0	15.579	10	40
145230	CRC-14	185	150	95	50	44.5	27.2	27.5	13.105	10	50
145240	CRC-15	150	150	150	70	45.1	27.9	30.2	10.685	5	30
145250	CRC-16*	185	120	185	95	53.7	33.2	35.2	25.700	5	25

* With rigid copper cable, it can also be used with the 240 mm² section (in the maximum of the principal).