

sofamel

Product Technical Specifications

Model OPL Strapping tool

Functionality

Tool to tighten and strips cutting.

Characteristics Raw Material




Chromed Stainless Steel. Ratchet Mechanism

Technical Specifications

Dimension: 350 mm

Weight: 1.45 Kg



Code	Ref.	 x 100	 Bag	 Box
406100	OPL	145	-	1



Model OPL

Strapping tool


Instructions for using the tool.

It is recommended to follow these instructions for optimal use of the tools:

1-Insert the strap into the plate. Be careful that the ears of the plate are in the opposite direction to the user.




2 - Manually wrap the product with the strap.




3 - Reinsert the strap into the plate under the strap initially inserted during **Stage 1**.

The strap must be over 5 cm after the plate.



4 - Fold the whole 5 cm of strap under the plate (manually or with a hammer).







Model OPL

Strapping tool


5 - Tighten the strap manually to correct the position "Strap + plate" assembly.




6 - Hold the tool firmly. The groove of the tensioner must be aligned with the cutting head slot.




7 - Insert the strap into the groove of the tool nose and into the tensioner.



8 - Position the strap completely to the left where the blades are to ensure a proper cut. Ideally, the right side of the strap should not be left out of the tool. Start tensioning the strap with the tension lever (left lever) holding the cutting lever firmly (right lever)



9 - If the strap is required to be retensioned, position the tension lever to position B. Then tighten the strap again.






Model OPL

Strapping tool


10 - When the tension is correct, position the tension lever in parallel with the cutting lever.



11 - Push the two levers forward to lock the strap on the plate.




12 - Hold the tension lever with your left hand and the cutting lever with your right hand.



13 - Push the cutting lever to cut the strap.



14 - If the strap has high mechanical properties, so it's better to press on the tool head with the left hand.





Model OPL

Strapping tool

15 - Push the tool forward to obtain a complete crimp. Then Remove the tool.



16 - The last stage: With a hammer, fold in the two ears of the plate.

