


Connections / Insulated terminals

11001 AT

Insulated ring terminal

AT terminals are manufactured from tinned electrolytic copper and insulated with flame-retardant PVC.

Color-coded according to DIN 46237 standard.



UL certified.

Code	Ref.	Section (mm ²)	Metric	Dimensions (mm)					Kg x1.000	Bag	Box
				d2	W	E	d1	L			
270100	AT-1,5/3	1.5	3	3.2	5.5	10.0	1.7	17.5	0.580	100	1600
270110	AT-1,5/4		4	4.3	6.6			19.4	0.620	100	1600
270120	AT-1,5/5		5	5.3	8.0			20.8	0.680	100	1600
270130	AT-1,5/6		6	6.4	10.0			23.0	0.850	100	1000
270140	AT-1,5/8		8	8.4	11.6			26.8	0.930	100	1000
270150	AT-1,5/10		10	10.5	13.6			30.5	-	100	1000
270160	AT-2,5/3	2.5	3	3.2	6.6	10.0	2.3	17.8	0.708	100	1400
270170	AT-2,5/4		4	4.3	6.6			19.4	0.710	100	1400
270180	AT-2,5/5		5	5.3	8.5			21.8	0.829	100	1200
270190	AT-2,5/6		6	6.4	11.0			26.8	1.172	100	1000
270200	AT-2,5/8		8	8.4	11.8			26.8	1.000	100	1000
270210	AT-2,5/10		10	10.5	13.6			30.5	-	100	1000
270220	AT-6/4	6.0	4	4.3	7.2	13.0	3.4	22.7	1.341	100	800
270230	AT-6/5		5	5.3	9.5			26.0	1.623	100	700
270240	AT-6/6		6	6.4	12.0			29.5	1.927	100	600
270250	AT-6/8		8	8.4	15.0			34.0	2.374	100	500
270260	AT-6/10		10	10.5	15.0			34.0	-	100	400