Connections / Insulated terminals


11002 AU

Insulated fork terminal

Ideal for quick screw connections without complete removal. Manufactured from tinned electrolytic copper with flame-retardant PVC insulation.

Color-coded according to DIN 46237 standard.

UL certified.





Code	Ref.	Section (mm²)	Metric	Dimensions (mm) d2	W	E	d1	L	x1.000	Bag	Box
275100	**AU-1,5/3**	0.5-1.5	3	3.2	5.7	10.0	1.7	21.0	0.660	100	1600
275110	**AU-1,5/4**		4	4.3	6.4			21.0	0.650	100	1600
275120	**AU-1,5/5**		5	5.3	8.1			21.0	0.680	100	1400
275130	**AU-1,5/6**		6	6.4	9.5			21.0	0.680	100	1400
275140	**AU-1,5/8**		8	-	-			-	1.000	100	1000
275160	**AU-2,5/3**	1.5-2.5	3	3.2	5.7	10.0	2.3	21.0	0.771	100	1400
275170	**AU-2,5/4**		4	4.3	6.4			21.0	0.748	100	1400
275180	**AU-2,5/5**		5	5.3	7.9			21.0	0.786	100	1200
275190	**AU-2,5/6**		6	6.4	9.3			21.0	0.781	100	1200
275200	**AU-2,5/8**		8	-	-			-	0.946	100	800
275220	**AU-6/4**	4-6	4	4.3	8.3	13.0	3.4	25.5	1.542	100	800
275230	**AU-6/5**		5	5.3	9.0			25.5	1.523	100	800
275240	**AU-6/6**		6	6.4	9.0			25.5	1.417	100	700
275250	**AU-6/8**		8	8.4	14.0			30.5	2.116	100	600