


Connections / Insulated terminals

11002 AU

Insulated fork terminal

Ideal for quick screw connections without complete removal. Manufactured from tinned electrolytic copper with flame-retardant PVC insulation.

Color-coded according to DIN 46237 standard.



UL certified.

Code	Ref.	Section (mm ²)	Metric	Dimensions (mm)					kg x1.000	Bag	Box
				d2	W	E	d1	L			
275100	AU-1,5/3	1.5	3	3.2	5.7	10.0	1.7	21.0	0.660	100	1600
275110	AU-1,5/4		4	4.3	6.4			21.0	0.650	100	1600
275120	AU-1,5/5		5	5.3	8.1			21.0	0.680	100	1400
275130	AU-1,5/6		6	6.4	9.5			21.0	0.680	100	1400
275140	AU-1,5/8		8	-	-			-	1.000	100	1000
275160	AU-2,5/3	2.5	3	3.2	5.7	10.0	2.3	21.0	0.771	100	1400
275170	AU-2,5/4		4	4.3	6.4			21.0	0.748	100	1400
275180	AU-2,5/5		5	5.3	7.9			21.0	0.786	100	1200
275190	AU-2,5/6		6	6.4	9.3			21.0	0.781	100	1200
275200	AU-2,5/8		8	-	-			-	0.946	100	800
275220	AU-6/4	6.0	4	4.3	8.3	13.0	3.4	25.5	1.542	100	800
275230	AU-6/5		5	5.3	9.0			25.5	1.523	100	800
275240	AU-6/6		6	6.4	9.0			25.5	1.417	100	700
275250	AU-6/8		8	8.4	14.0			30.5	2.116	100	600