

Connections / Copper connectors


10109 CPP

Connection tip isolated

CPP connectors are made from electrolytic copper tubing with a tin-plated surface finish for improved electrical contact.

The design facilitates connection of the cable lugs in the terminals.

The shape of the cable end facilitates cable insertion. The insulation provides an additional degree of protection.



UL certified.

Code	Ref.	Section (mm ²)	Dimensions (mm)							Kg x 100	Bag	Box
			ØE	ØI	L	L1	G	A	T			
025180	CPP-10	10	9.0	4.5	29.5	15.5	2.4	4.3	1.1	0.290	100	600
025190	CPP-16	16	10.5	5.9	35.0	19.0	2.6	5.5	1.2	0.470	100	300
025200	CPP-25	25	11.5	7.0	44.5	24.5	2.6	6.8	1.2	0.750	100	200
025210	CPP-35	35	14.0	8.7	54.0	29.5	3.2	8.0	1.5	1.320	50	150
025220	CPP-50	50	15.8	9.8	61.0	35.0	3.8	9.5	1.8	2.040	50	100
025230	CPP-70	70	18.0	11.6	75.0	44.0	4.2	11.0	2.0	3.310	25	50
025240	CPP-95	95	21.6	13.5	75.0	44.0	5.2	12.5	2.5	4.740	20	40