



032 TPE

Copper cable lug narrow palm

TPE cable lug manufactured from electrolytic copper with a tinplated finish to improve electrical contact. The narrow palm design makes it suitable for reduced spaces. According to IEC 61238-1-3 standard.

Code	Ref.	Section (mm ²)		Dimensions (mm)						Kg x 100	Bag	Box
				ØI	L	ØT	A	C1	C2			
032124	TPE-50/6	50	6	9,8	50,0	6,4	15,0	10,0	8,0	1,873	20	160
032125	TPE-50/8		8									
032126	TPE-50/10		10									
032130	TPE-70/6	70	6	11,5	55,0	6,4	15,0	12,0	8,0	2,881	20	100
032131	TPE-70/8		8									
032132	TPE-70/10		10									
032140	TPE-95/8	95	8	13,5	60,0	8,5	15,0	11,0	10,0	3,739	20	80
032145	TPE-95/10		10									
032149	TPE-120/8	120	8	15,6	65,0	8,5	21,0	10,0	11,0	6,186	10	60
032150	TPE-120/10		10									
032155	TPE-150/8	150	8	16,5	72,0	8,5	21,0	13,0	12,0	8,112	10	40
032160	TPE-150/10		10									
032161	TPE-150/12		12									
032170	TPE-185/10	185	10	18,9	75,0	10,5	26,0	13,0	12,0	9,710	10	30
032171	TPE-185/12		12									
032180	TPE-240/10	240	10	21,2	85,0	10,5	26,0	13,0	12,0	12,772	5	25
032181	TPE-240/12		12									