

Connections / Copper connectors


10108 TPE

Copper cable lug narrow palm

TPE terminals are manufactured from electrolytic copper tube with a tin-plated surface finish to ensure excellent conductivity.

Their narrow blade design allows installation in space-constrained applications, ensuring a reliable electrical connection even in demanding environments.

According to IEC 61238-1-1 standard.



Code	Ref.	Section (mm ²)		Dimensions (mm)						Kg x 100	Bag	Box
				ØI	L	ØT	A	C1	C2			
032125	TPE-50/8	50	8	9.8	50.0	8.5	15.0	10.0	8.0	1.826	20	160
032126	TPE-50/10		10									
032131	TPE-70/8	70	8	11.5	55.0	8.5	15.0	12.0	8.0	2.800	20	100
032132	TPE-70/10		10									
032140	TPE-95/8	95	8	13.5	60.0	8.5	15.0	11.0	10.0	3.739	20	80
032145	TPE-95/10		10									
032149	TPE-120/8	120	8	15.6	65.0	8.5	21.0	10.0	11.0	6.186	10	60
032150	TPE-120/10		10									
032155	TPE-150/8	150	8	16.5	72.0	8.5	21.0	13.0	12.0	8.112	10	40
032160	TPE-150/10		10									
032161	TPE-150/12	185	12	18.9	75.0	12.5	26.0	13.0	12.0	7.178	10	40
032170	TPE-185/10		10									
032171	TPE-185/12	240	12	21.2	85.0	12.5	26.0	13.0	12.0	9.570	10	30
032180	TPE-240/10		10									
032181	TPE-240/12	240	12	21.2	85.0	12.5	26.0	13.0	12.0	12.772	5	25
			10									