


Copper Connectors

Connections



10113 TCD

DIN 46235 copper cable lug

TCD cable lug manufactured from electrolytic copper with a tin-plated surface finish to improve electrical contact.

According to DIN 46235.



Code	Ref.	Section (mm ²)		Dimensions (mm)							Kg x 100	Bag	Box			
				ØE	ØI	L	ØT	A	L1	C						
005270	TCD-10/6	10	6	6.0	4.5	37.5	6.4	9.0	19.5	9.5	0.350	100	700			
005280	TCD-10/8		8			40.0	8.4	13.0	21.0	11.0				0.354	100	600
005320	TCD-16/6	16	6	8.5	5.5	46.5	6.4	13.0	18.5	9.5	1.194	50	250			
005330	TCD-16/8		8			49.0	8.4	13.0	23.0	11.0				1.206	50	250
005370	TCD-25/8	25	8	10.0	7.0	51.0	8.4	16.0	23.0	12.0	1.551	50	200			
005380	TCD-25/10		10			53.0	10.5	17.0	27.0	14.0				1.543	50	200
005420	TCD-35/8	35	8	12.5	8.2	55.0	8.4	17.5	23.0	12.0	3.010	20	120			
005430	TCD-35/10		10			57.0	10.5	19.0	27.0	14.0				2.997	20	120
005520	TCD-50/10	50	10	14.5	10	67.0	10.5	22.0	27.0	14.0	4.497	20	100			
005530	TCD-50/12		12			68.0	13.0	24.0	29.0	15.0				4.403	20	100
005580	TCD-70/10	70	10	16.5	11.5	70.0	10.5	24.0	27.0	14.0	6.029	20	60			
005590	TCD-70/12		12			71.0	13.0	24.0	27.0	14.0				6.065	20	60
005650	TCD-95/12	95	12	19.0	13.5	78.0	13.0	28.0	26.0	13.0	8.373	10	40			
005660	TCD-95/14		14			79.5	15.0	32.0	29.0	14.5				8.357	10	40
005670	TCD-95/16		16			81.0	17.0	32.0	32.0	16.0						
005700	TCD-120/10	120	10	21.0	15.5	85.0	10.5	30.0	27.0	14.0	10.728	10	30			
005710	TCD-120/12		12			86.0	13.0	30.0	29.0	15.0				10.436	10	30
005720	TCD-120/14		14			88.0	15.0	30.0	31.0	16.0						
005730	TCD-120/16		16			89.0	17.0	30.0	35.0	18.0				10.650	10	30
005760	TCD-150/12	150	12	23.5	17.0	94.0	13.0	34.0	29.0	15.0	13.374	10	20			
005770	TCD-150/14		14			96.0	15.0	34.0	31.0	16.0				15.514	10	20
005780	TCD-150/16		16			97.0	17.0	34.0	35.0	18.0						
005810	TCD-185/12	185	12	25.5	19.0	98.0	13.0	37.0	29.0	15.0	18.167	10	20			
005820	TCD-185/14		14			100.0	15.0	37.0	31.0	16.0				17.852	10	20
005830	TCD-185/16		16			101.0	17.0	37.0	35.0	18.0						
005860	TCD-240/12	240	12	29.0	21.5	108.0	13.0	42.0	29.0	15.0	25.766	5	10			
005870	TCD-240/14		14			110.0	15.0	42.0	31.0	16.0				25.780	5	10
005880	TCD-240/16		16			111.0	17.0	42.0	35.0	18.0						
005920	TCD-300/16	300	16	32.0	24.5	119.0	17.0	48.0	35.0	18.0	31.472	5	10			
005950	TCD-400/16*	400	16	38.5	27.5	140.0	17.0	55.0	45.0	24.0	53.380	2	4			
005980	TCD-500/16*	500	16	42.0	31.0	150.0	17.0	60.0	45.0	24.0	78.187	1	4			

*Not according to UL certified.