


Bimetallic Connectors

Connections



10401 TBE

Tinned aluminium cable lug

TBE cable lug manufactured from aluminium alloy tube of purity equal or higher than 99.5% with a tin-plated finish to improve electrical contact. Incorporates neutral grease to avoid aluminium oxidation.

Code	Ref.	Section (mm ²)	Dimensions (mm)					Kg x 100	Bag	Box
			ØE	ØI	ØT	L	A			
115090	TBE-16	16	8.7	5.5	8.5	43.0	15.0	0.437	1	400
115100	TBE-25	25	11.0	6.5	8.5	52.0	16.0	0.860	1	300
115110	TBE-35	35	13.3	7.8	8.5	56.0	19.0	1.360	1	250
115120	TBE-50	50	15.2	9.7	13.0	68.0	22.0	1.880	1	200
115130	TBE-70	70	17.0	11.0	13.0	75.0	25.0	2.700	1	200
115140	TBE-95	95	19.3	12.5	13.0	81.0	28.0	3.880	1	150
115150	TBE-120	120	21.7	14.1	13.0	94.0	32.0	5.600	1	100
115160	TBE-150	150	25.0	15.5	13.0	104.0	35.0	8.200	1	75
115170	TBE-185	185	28.1	18.3	13.0	112.0	40.0	10.600	1	50
115180	TBE-240	240	32.0	19.5	15.0	125.0	44.0	17.200	1	50
115190	TBE-300	300	34.0	23.3	15.0	140.0	47.0	20.700	1	40