
Connections / Aluminium connectors

10304 RJA

Aluminium joint

RJA butt connectors are manufactured from aluminium tubing with a purity of 99.5% or higher. They feature a stop that allows the conductors to be centred, dividing the connector into two symmetrical sections to facilitate crimping. Both ends are filled with neutral conductive grease to prevent aluminium oxidation and improve electrical conductivity.

According to UNE 211024 standard and certified with the AENOR mark.*





Code	Ref.	Section (mm²)	Dimensions (mm)			Kg x100	Bag	Box
			ØE	ØI	L			
095100	**RJ1A-25**	25	20.0	6.5	106.5	7.900	1	125
095110	**RJ1A-35**	35	20.0	8.0	106.5	7.600	1	125
095120	**RJ1A-50***	50	20.0	9.0	106.5	7.160	1	125
095130	**RJ1A-70**	70	20.0	11.0	106.5	7.000	1	125
095140	**RJ1A-95***	95	20.0	12.5	106.5	5.700	1	125
095150	**RJ2A-120**	120	25.0	13.7	133.0	13.000	1	90
095160	**RJ2A-150***	150	25.0	15.5	133.0	11.300	1	60
095170	**RJ4A-185**	185	32.0	17.0	143.5	22.000	1	50
095180	**RJ4A-240***	240	32.0	19.5	143.5	19.000	1	50
095190	**RJ5A-300**	300	40.0	23.3	218.0	48.000	1	15
095200	**RJ5A-400***	400	40.0	26.0	218.0	43.000	1	15