


Aluminium Connectors


Connections



10304 RJA

Aluminium joint

RJA joint manufactured from aluminium alloy of purity equal or higher than 99.5%. Incorporates a central buffer stop which divides the joint in two equal parts. Both holes contain neutral grease to avoid aluminium oxidation.

According to UNE 211024 standard.
Have  AENOR certified mark.*



Code	Ref.	Section (mm ²)	Dimensions (mm)			Kg x 100	Bag	Box
			ØE	ØI	L			
095100	RJ1A-25	25	20.0	6.5	106.5	7.900	1	125
095110	RJ1A-35	35	20.0	8.0	106.5	7.600	1	125
095120	RJ1A-50*	50	20.0	9.0	106.5	7.160	1	125
095130	RJ1A-70	70	20.0	11.0	106.5	7.000	1	125
095140	RJ1A-95*	95	20.0	12.5	106.5	5.700	1	125
095150	RJ2A-120	120	25.0	13.7	133.0	13.000	1	90
095160	RJ2A-150*	150	25.0	15.5	133.0	11.300	1	90
095170	RJ4A-185	185	32.0	17.0	143.5	22.000	1	50
095180	RJ4A-240*	240	32.0	19.5	143.5	19.000	1	50
095190	RJ5A-300	300	40.0	23.3	218.0	48.000	1	15
095200	RJ5A-400*	400	40.0	26.0	218.0	43.000	1	15