

Connections / ABC connectors



ABT/CT-240/240-2

ABT/CT-185/185-2

ABT/CT-150/150

ABT/CT-95/95

ABT/CT-150/35

ABT/CT-95/35

ABT/CT-95/10

ABT/CT-35/6

11101 ABT

Insulating piercing connector

ABT connectors are manufactured from PA 6.6 with fiberglass, providing excellent mechanical and thermal resistance. The toothed contacts, made of tinned aluminium, ensure excellent electrical conductivity. They allow safe piercing connections of main and tap cables without stripping. Suitable for low-voltage overhead cables. IP65 protection rating, suitable for outdoor use.

Easy installation



Code	Ref.	Section (mm ²)				Kg x 100	Bag	Box
		Main		Tap				
136090	ABT/CT-35/6	10	35	1,5	6	6,150	1	-
136091	ABT/CT-95/10	10	95	1,5	10	6,180	1	-
136120	ABT/CT-95/35	16	95	2,5	35	14,840	1	-
136130	ABT/CT-150/35	35	150	6	35	15,810	1	-
136140	ABT/CT-95/95	25	95	25	95	15,890	1	-
136142	ABT/CT-150/150	35	150	35	150	34,630	1	-
136150	ABT/CT-185/185-2	35	185	35	185	54,460	1	-
136152	ABT/CT-240/240-2	95	240	95	240	59,330	1	-

20106 ECP-M13

ABT/CP Connector Holding Handle

The ECP handle is an auxiliary tool used to hold and position ABT/CT piercing connectors during installation.

It is used with low-voltage ABT/CT piercing connectors. It helps keep the connector and cable correctly aligned during tightening, reducing assembly errors and the risk of faulty connections.



Code	Ref.	Dimensions (mm)	Weight (kg)
20106003	ECP-M13	230 x 55	0,40