

## 11101 ABT

### Insulating piercing connector

ABT connectors are manufactured from PA 6.6 with fiberglass, providing excellent mechanical and thermal resistance. The toothed contacts, made of tinned aluminium, ensure excellent electrical conductivity. They allow safe piercing connections of main and tap cables without stripping. Suitable for low-voltage overhead cables. IP65 protection rating, suitable for outdoor use.



ABT/CT-150/150

ABT/CT-185/185-2  
ABT/CT-240/240-2



ABT/CT-95/35  
ABT/CT-95/95  
ABT/CT-150/35

ABT/CT-35/6  
ABT/CT-95/10

Code	Ref.	Section (mm <sup>2</sup> )				Kg x 100	Bag	Box
		Main		Tap				
136090	ABT/CT-35/6	10	35	1.5	6	6.150	1	-
136091	ABT/CT-95/10	10	95	1.5	10	6.180	1	-
136120	ABT/CT-95/35	16	95	2.5	35	14.840	1	-
136130	ABT/CT-150/35	35	150	6	35	15.810	1	-
136140	ABT/CT-95/95	25	95	25	95	15.890	1	-
136142	ABT/CT-150/150	35	150	35	150	34.630	1	-
136150	ABT/CT-185/185-2	35	185	35	185	54.460	1	-
136152	ABT/CT-240/240-2	95	240	95	240	59.330	1	-