Hydraulic Tools

Electrohydraulic tools









| Battery type | Battery changer |
|---------------------|-----------------|
| 18 V 4.0 Ah, Li-ion | ASC 55 |

New generation battery operated hydraulic crimping tool

20202 EBC-13U

- Universal crimping head for all types of crimping, including deep staggered punch crimping.
- 180 degree swivel head.
- 2-speed hydraulic system.
- Independently designed oil return system can safety retract
- without electricity.
- The trigger switch and return button are separately and activated by only one hand.
- Built-in chip, with memory function, can stop automatically when crimping is completed, realize intelligent crimping.
- Crimping cycle data is automatically stored on a memory card for transfer to PC by USB interface or bluetooth.
- OLED display provides battery capacity, operational and service crimping cycled, bluetooth information, etc.
- Automatic retraction when the maximum pressure is reached.
- LED lightning for work in dark environments.
- Rubber grip to have low noise and minimal vibration.
- Include tool holder briefcase.





Includes AD-13U/13C adapter to convert "H" head to "C" head.

| Code | Ref. | Nominal Pressure | Maximum crimping force | Tool dimensions | Briefcase dimensions | Tool weight | Briefcase weight |
|--------|---------|---------------------|------------------------|--------------------|----------------------|---------------------------|------------------|
| 412003 | EBC-13U | 70 MPa | 130 kN | 363x334x95 mm | 670x470x135 mm | 6.7 kg (incl. battery) | 4.5 kg |

Crimping range

| Copper lugs and splices | 400 mm ² | Bimetallic lugs (Stepped deep punching) | 240 mm ² |
|----------------------------|---------------------|---|---------------------|
| Aluminium lugs and splices | 300 mm ² | H type, C type clamps | 240 mm ² |

Available dies



HD13 copper and aluminium cable lugs and butt-connectors by hexagonal compression

Copper: up to 400 mm² Aluminium: up to 300 mm² Bimetallic: up to 240 mm²



CD13 copper and aluminium compression clamps by circular compression Copper: Up to 185 mm²
Aluminium: Main up to 300 mm² and tap up to 70 mm²



MP-L/PP bimetallic cable lugs by deep punching compression Up to 240 mm²

MP-S/PP aluminium multi voltage joints by deep punching compression Up to 240 mm²

Note: choose the adapter according to section, to be used together with the corresponding punch and die.