Insulating Poles Safety

Connectable poles



Metric-10 Head



Universal Head



BBayonet Head



P Multipurpose Head (Hexagonal + Metric head-10)

INDOOR and OUTDOOR Use in dry and humid environment

Connectable pole with two sections made of polyester and fibreglass tube Ø 32 mm with humidity-proof seals on each end, hand protector, grip, tip, 3 deflecting hoods and M (Metric-10), U (Universal), B (Bayonet) or P (Hexagonal + Metric-10) head.

30805 BMAE-2

- Total length: 2 meters
- Composed of 2 sections of 1 m each
- Working voltage: 30 kV
- For INDOOR and OUTDOOR use in dry and humid environment

| Code | Ref. |
|--------|------------|
| 616200 | BMAE-2/30M |
| 616201 | BMAE-2/30U |
| 616202 | BMAE-2/30B |
| 616203 | BMAE-2/30P |

30805 BMAE-2,5

- Total length: 2.5 meters
- Composed of 1 section of 1 m + 1 section of 1.5 m
- Working voltage: 66 kV
- For INDOOR and OUTDOOR use in dry and humid environment

| Code | Ref. |
|--------|--------------|
| 616210 | BMAE-2,5/66M |
| 616211 | BMAE-2,5/66U |
| 616212 | BMAE-2,5/66B |
| 616213 | BMAE-2,5/66P |

30805 BMAE-3

- Total length: 3 meters
- Composed of 2 sections of 1.5 m each
- Working voltage: 110 kV
- For INDOOR and OUTDOOR use in dry and humid environment

| Code | Ref. |
|--------|-------------|
| 616220 | BMAE-3/110M |
| 616221 | BMAE-3/110U |
| 616222 | BMAE-3/110B |
| 616223 | BMAE-3/110P |

