

sofamel

Product Technical Specifications


Mod. BMAE Connectable Poles

Functionality

The connectable poles have the function of safeguarding distances of electrical work. These poles have a fixed length but with two sections. With them the operator can make the detection and earthing (voltage detector and earthing equipment is required) at a safe distance.

Product Features

Connectable pole, composed of two sections made of polyester and fibreglass tube Ø 40 mm with hand protector, grip, tip, 3 deflecting hoods and M (Metric-10), U (Universal), B (Bayonet) or P (Hexagonal + Metric-10) head. Indoor and outdoor use.



M
Cabezal Métrico-10



U
Cabezal Universal



B
Cabezal Bayoneta



P
Cabezal Polivalente
(Hexagonal + Métrico-10)





Mod. BMAE

Connectable Poles

Raw Material Features

Insulating tube: **made of polyester and fiberglass.**

Blocking handles: **polyamide PA66-GF30.**

Deflecting hoods: **EPDM rubber.**

Connector: **anodized aluminum.**

Screw: **stainless steel.**

Certified

Manufactured following the established by Standard **UNE-EN 50508** - Points **4.2, 4.3, 4.4** (in dry conditions) and **4.5**. Multi-purpose insulating sticks for electrical operations on high voltage installations.

Electrical Features

Ref.	Length	Working voltage
BMAE-3V	3 m (2 sections of 1,5 m)	132 kV
BMAE-4V	4 m (2 sections 2 m)	220 kV
BMAE-5V	5 m (2 sections of 2 m + 1 section of 1 m)	380 kV
BMAE-6V	6 m (2 sections of 1,5 m)	380 kV

Datos sujetos a cambios
2017, Mayo 2

Versión: R2-7.2 COM01

Thomas Alva Edison, 16-17 - Pol. Industrial Plans d'Arau - 08787 La Pobla de Claramunt (Barcelona) - Spain
Tel. +34 93 808 79 80 - Info@sofamel.es
www.sofamel.com

© 2017 Sofamel SLU
Todos los derechos reservados.

Las especificaciones están sujetas a cambios sin previo aviso.