


## 005 TCD

### Cosses DIN 46235 en cuivre renforcé

Les cosses en cuivre à plage 2 trous sont fabriquées en cuivre électrolytique avec un revêtement superficiel étamé afin d'améliorer le contact électrique.  
Conformes à la norme DIN 46235.



| Code   | Réf.      | Section (mm <sup>2</sup> ) |    | Dimensions (mm) |      |      |      |      |      |      | Kg<br>x 100 | Sac | Boîte |
|--------|-----------|----------------------------|----|-----------------|------|------|------|------|------|------|-------------|-----|-------|
|        |           |                            |    | ØE              | ØI   | L    | ØT   | A    | L1   | C    |             |     |       |
| 005220 | TCD-6/5   | 6                          | 5  | 5,5             | 3,8  | 33,0 | 5,3  | 8,5  | 15,0 | 8,0  | 0,319       | 100 | 1000  |
| 005230 | TCD-6/6   |                            | 6  |                 |      | 34,5 | 6,4  | 8,5  | 18,5 | 9,5  | 0,317       | 100 | 1000  |
| 005240 | TCD-6/8   |                            | 8  |                 |      | 37,0 | 8,4  | 8,5  | 23,0 | 12,0 | 0,322       | 100 | 800   |
| 005260 | TCD-10/5  | 10                         | 5  | 6,0             | 4,5  | 36,0 | 5,3  | 9,0  | 15,0 | 8,0  | 0,353       | 100 | 700   |
| 005270 | TCD-10/6  |                            | 6  |                 |      | 37,5 | 6,4  | 9,0  | 19,5 | 9,5  | 0,350       | 100 | 700   |
| 005280 | TCD-10/8  |                            | 8  |                 |      | 40,0 | 8,4  | 9,0  | 21,0 | 12,0 | 0,354       | 100 | 600   |
| 005320 | TCD-16/6  | 16                         | 6  | 8,5             | 5,5  | 46,5 | 6,4  | 13,0 | 18,5 | 9,5  | 1,194       | 50  | 250   |
| 005330 | TCD-16/8  |                            | 8  |                 |      | 49,0 | 8,4  | 13,0 | 23,0 | 12,0 | 1,206       | 50  | 250   |
| 005340 | TCD-16/10 |                            | 10 |                 |      | 51,0 | 10,5 | 17,0 | 27,0 | 14,0 | 1,210       | 50  | 250   |
| 005350 | TCD-16/12 |                            | 12 |                 |      | 53,0 | 13,0 | 17,0 | 29,0 | 15,0 | 1,889       | 50  | 200   |
| 005360 | TCD-25/6  | 25                         | 6  | 10,0            | 7,0  | 48,5 | 6,4  | 14,0 | 18,5 | 9,5  | 1,520       | 50  | 200   |
| 005370 | TCD-25/8  |                            | 8  |                 |      | 51,0 | 8,4  | 16,0 | 23,0 | 12,0 | 1,551       | 50  | 200   |
| 005380 | TCD-25/10 |                            | 10 |                 |      | 53,0 | 10,5 | 17,0 | 27,0 | 14,0 | 1,543       | 50  | 200   |
| 005390 | TCD-25/12 |                            | 12 |                 |      | 54,0 | 13,0 | 19,0 | 29,0 | 15,0 | 1,490       | 50  | 200   |
| 005410 | TCD-35/6  | 35                         | 6  | 12,5            | 8,2  | 55,0 | 6,4  | 17,5 | 23,0 | 12,0 | 3,070       | 20  | 140   |
| 005420 | TCD-35/8  |                            | 8  |                 |      | 55,0 | 8,4  | 17,5 | 23,0 | 12,0 | 3,010       | 20  | 120   |
| 005430 | TCD-35/10 |                            | 10 |                 |      | 57,0 | 10,5 | 19,0 | 27,0 | 14,0 | 2,997       | 20  | 120   |
| 005440 | TCD-35/12 |                            | 12 |                 |      | 58,0 | 13,0 | 21,0 | 29,0 | 15,0 | 2,959       | 20  | 120   |
| 005450 | TCD-35/14 |                            | 14 |                 |      | 58,0 | 15,0 | 21,0 | 29,0 | 15,0 | 2,806       | 20  | 120   |
| 005510 | TCD-50/8  | 50                         | 8  | 14,5            | 10,0 | 65,0 | 8,4  | 20,0 | 23,0 | 12,0 | 4,498       | 20  | 100   |
| 005520 | TCD-50/10 |                            | 10 |                 |      | 67,0 | 10,5 | 22,0 | 27,0 | 14,0 | 4,497       | 20  | 100   |
| 005530 | TCD-50/12 |                            | 12 |                 |      | 68,0 | 13,0 | 24,0 | 29,0 | 15,0 | 4,403       | 20  | 100   |
| 005540 | TCD-50/14 |                            | 14 |                 |      | 71,0 | 15,0 | 28,0 | 35,0 | 18,0 | 4,455       | 20  | 100   |
| 005550 | TCD-50/16 |                            | 16 |                 |      | 71,0 | 17,0 | 28,0 | 35,0 | 18,0 | 4,297       | 20  | 80    |
| 005570 | TCD-70/8  |                            | 8  |                 |      | 68,0 | 8,4  | 24,0 | 23,0 | 12,0 | 5,992       | 20  | 60    |
| 005580 | TCD-70/10 | 70                         | 10 | 16,5            | 11,5 | 70,0 | 10,5 | 24,0 | 27,0 | 14,0 | 6,029       | 20  | 60    |
| 005590 | TCD-70/12 |                            | 12 |                 |      | 71,0 | 13,0 | 24,0 | 27,0 | 14,0 | 6,065       | 20  | 60    |
| 005600 | TCD-70/14 |                            | 14 |                 |      | 74,0 | 15,0 | 30,0 | 35,0 | 18,0 | 5,972       | 20  | 60    |
| 005610 | TCD-70/16 |                            | 16 |                 |      | 74,0 | 17,0 | 30,0 | 35,0 | 18,0 | 5,842       | 20  | 60    |
| 005630 | TCD-95/8  |                            | 8  |                 |      | 77,0 | 8,4  | 28,0 | 24,0 | 12,0 | 8,918       | 10  | 40    |
| 005640 | TCD-95/10 | 95                         | 10 | 19,0            | 13,5 | 77,0 | 10,5 | 28,0 | 24,0 | 12,0 | 8,470       | 10  | 40    |
| 005650 | TCD-95/12 |                            | 12 |                 |      | 78,0 | 13,0 | 28,0 | 26,0 | 13,0 | 8,373       | 10  | 40    |
| 005660 | TCD-95/14 |                            | 14 |                 |      | 79,5 | 15,0 | 32,0 | 29,0 | 14,5 | 8,357       | 10  | 40    |
| 005670 | TCD-95/16 |                            | 16 |                 |      | 81,0 | 17,0 | 32,0 | 32,0 | 16,0 | 8,596       | 10  | 40    |



## 005 TCD

### Cosses DIN 46235 en cuivre renforcé

Les cosses en cuivre à plage 2 trous sont fabriquées en cuivre électrolytique avec un revêtement superficiel étamé afin d'améliorer le contact électrique. Conformées à la norme DIN 46235.



| Code   | Réf.         | Section (mm²) |    | Dimensions (mm) |      |       |      |      |      |      | Kg<br>x 100 | Sac | Boîte |
|--------|--------------|---------------|----|-----------------|------|-------|------|------|------|------|-------------|-----|-------|
|        |              |               |    | ØE              | ØI   | L     | ØT   | A    | L1   | C    |             |     |       |
| 005700 | TCD-120/10   | 120           | 10 | 21,0            | 15,5 | 85,0  | 10,5 | 30,0 | 27,0 | 14,0 | 10,728      | 10  | 30    |
| 005710 | TCD-120/12   |               | 12 |                 |      | 86,0  | 13,0 | 30,0 | 29,0 | 15,0 | 10,436      | 10  | 30    |
| 005720 | TCD-120/14   |               | 14 |                 |      | 88,0  | 15,0 | 30,0 | 31,0 | 16,0 | 10,820      | 10  | 30    |
| 005730 | TCD-120/16   |               | 16 |                 |      | 89,0  | 17,0 | 30,0 | 35,0 | 18,0 | 10,650      | 10  | 30    |
| 005740 | TCD-120/20   |               | 20 |                 |      | 92,0  | 21,0 | 38,0 | 42,0 | 21,0 | 10,627      | 10  | 30    |
| 005750 | TCD-150/10   | 150           | 10 | 23,5            | 17,0 | 93,0  | 10,5 | 34,0 | 27,0 | 14,0 | 15,554      | 10  | 20    |
| 005760 | TCD-150/12   |               | 12 |                 |      | 94,0  | 13,0 | 34,0 | 29,0 | 15,0 | 13,374      | 10  | 20    |
| 005770 | TCD-150/14   |               | 14 |                 |      | 96,0  | 15,0 | 34,0 | 31,0 | 16,0 | 15,514      | 10  | 20    |
| 005780 | TCD-150/16   |               | 16 |                 |      | 97,0  | 17,0 | 34,0 | 35,0 | 18,0 | 15,436      | 10  | 20    |
| 005790 | TCD-150/20   |               | 20 |                 |      | 100,0 | 21,0 | 40,0 | 42,0 | 21,0 | 15,269      | 10  | 20    |
| 005800 | TCD-185/10   | 185           | 10 | 25,5            | 19,0 | 97,0  | 10,5 | 37,0 | 27,0 | 14,0 | 18,228      | 10  | 20    |
| 005810 | TCD-185/12   |               | 12 |                 |      | 98,0  | 13,0 | 37,0 | 29,0 | 15,0 | 18,167      | 10  | 20    |
| 005820 | TCD-185/14   |               | 14 |                 |      | 100,0 | 15,0 | 37,0 | 31,0 | 16,0 | 17,852      | 10  | 20    |
| 005830 | TCD-185/16   |               | 16 |                 |      | 101,0 | 17,0 | 37,0 | 35,0 | 18,0 | 18,227      | 10  | 20    |
| 005840 | TCD-185/20   |               | 20 |                 |      | 104,0 | 21,0 | 40,0 | 42,0 | 21,0 | 17,732      | 10  | 20    |
| 005860 | TCD-240/12   | 240           | 12 | 29,0            | 21,5 | 108,0 | 13,0 | 42,0 | 29,0 | 15,0 | 25,766      | 5   | 10    |
| 005870 | TCD-240/14   |               | 14 |                 |      | 110,0 | 15,0 | 42,0 | 31,0 | 16,0 | 25,780      | 5   | 10    |
| 005880 | TCD-240/16   |               | 16 |                 |      | 111,0 | 17,0 | 42,0 | 35,0 | 18,0 | 26,587      | 5   | 10    |
| 005890 | TCD-240/20   |               | 20 |                 |      | 114,0 | 21,0 | 45,0 | 42,0 | 21,0 | 25,808      | 5   | 10    |
| 005910 | TCD-300/14   | 300           | 14 | 32,0            | 24,5 | 117,0 | 15,0 | 48,0 | 33,0 | 17,0 | 31,931      | 5   | 10    |
| 005920 | TCD-300/16   |               | 16 |                 |      | 119,0 | 17,0 | 48,0 | 35,0 | 18,0 | 31,472      | 5   | 10    |
| 005930 | TCD-300/20   |               | 20 |                 |      | 122,0 | 21,0 | 48,0 | 42,0 | 21,0 | 31,490      | 5   | 10    |
| 005945 | TCD-400/14*  | 400           | 14 | 38,5            | 27,5 | 140,0 | 15,0 | 55,0 | 45,0 | 24,0 | 60,955      | 2   | 4     |
| 005950 | TCD-400/16*  |               | 16 |                 |      | 140,0 | 17,0 | 55,0 | 45,0 | 24,0 | 53,380      | 2   | 4     |
| 005960 | TCD-400/20*  |               | 20 |                 |      | 140,0 | 21,0 | 55,0 | 45,0 | 24,0 | 64,515      | 2   | 4     |
| 005980 | TCD-500/16*  | 500           | 16 | 42,0            | 31,0 | 150,0 | 17,0 | 60,0 | 45,0 | 24,0 | 78,187      | 1   | 4     |
| 005981 | TCD-500/20*  |               | 20 |                 |      | 150,0 | 21,0 | 60,0 | 45,0 | 24,0 | 77,060      | 1   | 4     |
| 005988 | TCD-625/16*  | 625           | 16 | 44,0            | 34,5 | 160,0 | 17,0 | 64,0 | 45,0 | 24,0 | 77,880      | 1   | 3     |
| 005990 | TCD-625/20*  |               | 20 |                 |      | 160,0 | 21,0 | 64,0 | 45,0 | 24,0 | 76,670      | 1   | 3     |
| 005994 | TCD-800/16*  | 800           | 16 | 52,0            | 40,0 | 190,0 | 17,0 | 75,0 | 45,0 | 24,0 | 142,020     | 1   | 10    |
| 005995 | TCD-800/20*  |               | 20 |                 |      | 190,0 | 21,0 | 75,0 | 45,0 | 24,0 | 140,850     | 1   | 10    |
| 005998 | TCD-1000/16* | 1000          | 16 | 58,0            | 44,0 | 190,0 | 17,0 | 84,0 | 45,0 | 24,0 | 186,090     | 1   | 10    |
| 005999 | TCD-1000/20* |               | 20 |                 |      | 190,0 | 21,0 | 84,0 | 45,0 | 24,0 | 185,790     | 1   | 10    |

\* Non conforme au certificat UL.